
mosromgr

Release 0.8.1

unknown

Apr 15, 2021

CONTENTS

1 Example Usage	3
2 Documentation	5
3 Issues and questions	63
4 Contributing	65
5 Contributors	67
6 Licence	69
7 Contact	71
Python Module Index	73
Index	75

Python library for managing MOS running orders. Pronounced *mos-ro-manager*.



The library provides functionality for classifying MOS file types, processing and inspecting MOS message files, as well as merging MOS files into a running order, and providing a “completed” programme including all additions and changes made between the first message (`roCreate`) and the last (`roDelete`).

This can be used as a library, using the utilities provided in the `mosromgr` module, and the command line command `Command line interface` can be used to process either a directory of MOS files, or a folder within an S3 bucket.

This library was developed by the [BBC News Labs](#) team.

Warning: Note that the library is currently in beta. The API and CLI are not yet stable and may change. Once the library reaches v1.0, it will be considered stable. Please consider giving [Feedback](#) to help stabilise the API.

EXAMPLE USAGE

1.1 Command line

List the stories within a running order:

```
$ mosromgr inspect -f roCreate.mos.xml --stories
0828 MIDLANDS TODAY Wed, 11.11.2020

INTRODUCTION-READ

TESTING-OOV

WEATHER-SHORT

END OF PROGRAMME
```

Merge all MOS files in directory *newsnight* and save in FINAL.xml:

```
$ mosromgr merge -f newsnight/* -o FINAL.xml
```

1.2 Library

Load a `roCreate` file and view its stories:

```
from mosromgr.mostypes import RunningOrder

ro = RunningOrder.from_file('roCreate.mos.xml')

for story in ro.stories:
    print(story.slug)
```

Merge a single `roStorySend` (*StorySend*) into a `roCreate` (*RunningOrder*) and output the file to a new file:

```
from mosromgr.mostypes import RunningOrder, StorySend

ro = RunningOrder.from_file('roCreate.mos.xml')
ss = StorySend.from_file('roStorySend.mos.xml')

ro += ss
```

(continues on next page)

(continued from previous page)

```
with open('final.mos.xml', 'w') as f:  
    f.write(str(ro))
```

If you're automating this process you won't necessarily know which MOS Type to use, so you can construct an object from the base class *MosFile* which will automatically classify your file:

```
>>> from mosromgr.mostypes import MosFile  
>>> mf1 = MosFile.from_file('roCreate.mos.xml')  
>>> mf1  
<RunningOrder 1000>  
>>> mf2 = MosFile.from_file('roStorySend.mos.xml')  
>>> mf2  
<StorySend 1001>
```

Using *MosCollection* will sort and classify multiple MOS types of all given files, allowing you to process a collection of MOS files within a complete or partially complete programme:

```
from mosromgr.moscollection import MosCollection  
  
mos_files = ['roCreate.mos.xml', 'roStorySend.mos.xml', 'roDelete.mos.xml']  
mc = MosCollection.from_files(mos_files)  
  
mc.merge()  
with open('final.mos.xml', 'w') as f:  
    f.write(str(mc))
```

DOCUMENTATION

This documentation follows the [Diátaxis](#) system, so is split between four modes of documentation: tutorials, how-to guides, technical reference and explanation.

2.1 Getting started

This section shows you how to get started with *mosromgr*.

2.1.1 Installing

Install with pip:

```
$ pip install mosromgr
```

2.1.2 Command line interface check

After installing the module, a simple way to verify it's working is by using the *Command line interface*. First of all, open a terminal and run the command `mosromgr` to be sure it's installed. You should see output like so:

```
$ mosromgr
optional arguments:
  -h, --help            show this help message and exit
  --version           show program's version number and exit

commands:
{help,detect,inspect,merge}
  help                  Displays help about the specified command
  detect                Detect the MOS type of one or more files
  inspect              Inspect the contents of a roCreate file
  merge                Merge the given MOS files
```

Now start by obtaining the MOS files for a single complete programme. In a terminal window, enter the directory containing the MOS files and run the command `mosromgr detect` on a single roCreate file, for example:

```
$ mosromgr detect 123456-roCreate.mos.xml
123456-roCreate.mos.xml: RunningOrder
```

The output shows that it's identified the roCreate file as a *RunningOrder*. Try it with some other files to check it can correctly identify a *MosFile* subclass to represent the file.

2.1.3 Using the module in Python code

Now you've tested the ready-made command line program is working with your MOS file, try using the module in some custom Python code.

Open a Python shell and try creating a MOS object from your `roCreate` file:

```
>>> from mosromgr.mostypes import RunningOrder
>>> ro = RunningOrder.from_file('123456-roCreate.mos.xml')
>>> ro
<RunningOrder 123456>
```

This shows you've successfully loaded a MOS file and created a `RunningOrder` from it. The output shows the object representation (`__repr__`) which includes the class name and message ID (this is from the XML contents, not the filename).

The next page will walk through the functionality provided by the module.

2.2 Introduction

This section is a walkthrough of the contents of the module, intended to explain how `mosromgr` works and introduce the concepts.

2.2.1 MOS Types

The [API - MOS Types](#) section of the module provides a collection of classes for dealing with individual MOS messages. The classes provide easy access to some of the elements within a MOS file, such as a list of stories within a running order, the transmission time of a programme, or its duration.

For example, you can load a running order from a `roCreate` file, print the RO Slug and access some details:

```
>>> from mosromgr.mostypes import RunningOrder
>>> ro = RunningOrder.from_file('123456-roCreate.mos.xml')
>>> ro.ro_slug
'22:45 NEWSNIGHT 54D CORE Thu, 08.04.2021'
>>> ro.message_id
123456
>>> ro.start_time
datetime.datetime(2021, 4, 8, 21, 46, 30)
>>> ro.duration
970.0
>>> len(ro.stories)
10
```

In the case of MOS messages which contain a *change* to a running order, the relevant details are exposed, for example a `StoryInsert` includes access to the `source_stories` and `target_story`.

When dealing with merging `MosFile` objects, this is done by “adding” each file to the `RunningOrder` object by using the `+` operator:

```
>>> from mosromgr.mostypes import RunningOrder, StoryInsert
>>> ro = RunningOrder.from_file('123456-roCreate.mos.xml')
>>> ss = StoryInsert.from_file('123457-roStoryInsert.mos.xml')
>>> len(ro.stories)
10
```

(continues on next page)

(continued from previous page)

```
>>> ro += ss
>>> len(ro.stories)
11
```

2.2.2 MOS Elements

The *API - MOS Elements* part of the module provides a collection of classes used to provide easy access to certain elements within a *MosFile* object, such as a list of stories within a running order, and the items within a story:

```
from mosromgr.mostypes import RunningOrder

ro = RunningOrder.from_file('123456-roCreate.mos.xml')

print(ro.ro_slug)
for story in ro.stories:
    print(story.slug)
```

Here, `ro.stories` is a list of *Story* objects. Each story has its own set of accessible properties, such as the story's `duration`, `start_time`, `end_time`, `offset` and `items`:

```
>>> story = ro.stories[0]
>>> story.duration
180.0
>>> story.start_time
datetime.datetime(2021, 4, 8, 21, 46, 30)
>>> len(story.items)
3
```

Here, the story contains 3 items, each of these is an *Item* object.

2.2.3 MOS Collection

The *API - MOS Collection* part of the module provides a wrapper class *MosCollection* which stores references to specified MOS files, strings or S3 object keys so the *MosFile* objects can be recreated when needed rather than kept in memory. Rather than using the + operator, a `merge()` method is provided:

```
from mosromgr.moscollection import MosCollection

mc = MosCollection.from_s3(bucket_name=bucket_name, prefix=prefix)

mc.merge()
```

The next page will cover some example problems and solutions to show you how you can use *mosromgr* in practice.

2.3 How-to guide

This section is a series of helpful recipes for how to do things and solve particular problems with *mosromgr*.

Note: These examples deal with MOS messages read from local files, but *MosFile* and *MosCollection* objects can also be constructed using *from_string* and *from_s3*. Refer to *API - MOS Types* and *API - MOS Collection* for more information.

2.3.1 Merging MOS files

When dealing with merging *MosFile* objects, this is done by “adding” each file to the *RunningOrder* object by using the + operator:

```
>>> from mosromgr.mostypes import RunningOrder, StoryInsert
>>> ro = RunningOrder.from_file('123456-roCreate.mos.xml')
>>> ss = StoryInsert.from_file('123457-roStoryInsert.mos.xml')
>>> len(ro.stories)
10
>>> ro += ss
>>> len(ro.stories)
11
```

To parse and merge a collection of MOS files, you could create a list of files (or use *glob()*), let *MosFile* classify each file, then merge each of them into the *RunningOrder*:

```
from mosromgr.mostypes import MosFile
from glob import glob

files = glob('*mos.xml')

ro, *mosfiles = sorted(MosFile.from_file(f) for f in files)

for mf in mosfiles:
    ro += mf
```

To access the final XML, simply print the *RunningOrder* object or access the *__str__*:

```
>>> print(ro)
<mos>
  <mosID>MOS ID</mosID>
  <messageID>1234567</messageID>
  ...
>>> s = str(ro)
>>> s
<mos>
  <mosID>MOS ID</mosID>
  <messageID>1234567</messageID>
  ...
```

2.3.2 Merging MOS files using MOSCollection

The `MosCollection` class provides a wrapper for operations dealing with a collection of MOS files as part of one programme. So to merge files like in the previous example, you could do the following instead:

```
from mosromgr.moscollection import MosCollection
from glob import glob

files = glob('*.mos.xml')
mc = MosCollection.from_files(files)

mc.merge()
```

To access the final XML, simply print the `MosCollection` object or access the `__str__`:

```
>>> print(mc)
<mos>
  <mosID>MOS ID</mosID>
  <messageID>1234567</messageID>
  ...
>>> s = str(mc)
>>> s
<mos>
  <mosID>MOS ID</mosID>
  <messageID>1234567</messageID>
  ...
```

2.3.3 Accessing the properties of a running order

For example, a `RunningOrder` object could contain several `Story` objects, each containing a number of `Item` objects:

```
>>> from mosromgr.mostypes import RunningOrder
>>> ro = RunningOrder.from_file('roCreate.mos.xml')
>>> ro.stories
[<Story 1234>, <Story 1235>, <Story 1236>]
>>> [story.duration for story in ro.stories]
[10, 20, 30]
>>> ro.duration
60
>>> story = ro.stories[0]
>>> story.slug
'Some story'
>>> story.items
[<Item ITEM1>, <Item ITEM2>, <Item ITEM3>]
>>> item = story.items[0]
>>> item.slug
'Some item'
```

In the case of a `StoryAppend` object, this would contain a single story:

```
>>> from mosromgr.mostypes import StoryAppend
>>> sa = StoryAppend.from_file('roStoryAppend.mos.xml')
>>> sa.story
<Story STORY1>
```

(continues on next page)

(continued from previous page)

```
>>> sa.duration  
20
```

If this `StoryAppend` object was merged with a `RunningOrder` object, the new story would be accessible in the `RunningOrder.stories` property:

```
>>> from mosromgr.mostypes import RunningOrder, StoryAppend  
>>> ro = RunningOrder.from_file('roCreate.mos.xml')  
>>> sa = StoryAppend.from_file('roStoryAppend.mos.xml')  
>>> len(ro.stories)  
3  
>>> ro += sa  
>>> len(ro.stories)  
4
```

Note: Note that these classes should not normally be constructed by the user, but instances of them can be found within `MosFile` objects, so the following documentation is provided as a reference to how they can be used.

Note: Note that additional information may be contained within the XML, and these elements are simply an abstraction providing easy access to certain elements. In the spirit of escape hatches and ejector seats, the original XML in which the element was found is accessible as an `xml.etree.ElementTree.Element` object for further introspection.

2.3.4 Handling Exceptions

This can be useful for handling exceptions in your own code. For example, to handle any exception generated by the library, you can catch the library's base exception `MosRomgrException`:

```
try:  
    main()  
except MosRomgrException as e:  
    print(e)
```

To catch a specific exception known to be raised under certain circumstances, each exception can be imported and handled separately if required:

```
from mosromgr.mostypes import MosFile  
from mosromgr.exc import MosInvalidXML, UnknownMosFileType  
  
try:  
    ro = MosFile.from_file(mosfile)  
except MosInvalidXML as e:  
    print("Invalid in", mosfile)  
except UnknownMosFileType as e:  
    print("Unknown MOS file type", mosfile)
```

In some cases, a warning is raised rather than an exception. This means that execution is continued but a warning is output, which can be suppressed using the `warnings` module.

2.3.5 Capturing warnings

If you want to catch warnings and log them (for example, during a merge), you can use `warnings.catch_warnings`:

```
with warnings.catch_warnings(record=True) as warns:
    mc.merge()

warning_messages = [str(w.message) for w in warns]
```

2.3.6 Suppressing warnings

If you are not interested in seeing or capturing warnings, you can either use a `warning filter` or use `warnings.catch_warnings`:

```
with warnings.catch_warnings() as warns:
    mc.merge()
```

2.3.7 Using the command line interface

The `mosromgr` command provided includes a number of subcommands. Running `mosromgr` alone will show the general help message, and running a subcommand without arguments will show the help message for that subcommand.

Detecting MOS file types

To detect the type of a MOS file, use the `mosromgr detect` command:

```
$ mosromgr detect -f 123456-roCreate.mos.xml
123456-roCreate.mos.xml: RunningOrder
```

Multiple files can be provided as arguments:

```
$ mosromgr detect -f 123456-roCreate.mos.xml 123457-roStorySend.mos.xml
123456-roCreate.mos.xml: RunningOrder
123457-roStorySend.mos.xml: StorySend
```

Wildcards can also be used:

```
$ mosromgr detect *
123456-roCreate.mos.xml: RunningOrder
123457-roStorySend.mos.xml: StorySend
...
9148627-roDelete.mos.xml: RunningOrderEnd
bbcProgrammeMetadata.xml: Unknown MOS file type
cricket: Invalid
FINAL.json: Invalid
FINAL.xml: RunningOrder (completed)
```

You can also read files from an S3 bucket. Either a specific file by key:

```
$ mosromgr detect -b my-bucket -k newsnight/20210101/123456-roCreate.mos.xml
INFO:botocore.credentials:Found credentials in environment variables.
OPENMEDIA_NCS.W1.BBC.MOS/OM_10.1253459/5744992-roCreate.mos.xml: RunningOrder
```

Or a whole folder by prefix:

```
$ mosromgr detect -b bbc-newslabs-slicer-mos-message-store -p newsnight/20210101/
INFO:botocore.credentials:Found credentials in environment variables.
newsnight/20210101/123456-roCreate.mos.xml: RunningOrder
newsnight/20210101/123457-roStorySend.mos.xml: StorySend
newsnight/20210101/123458-roStorySend.mos.xml: StorySend
newsnight/20210101/123459-roStorySend.mos.xml: StorySend
...
```

Inspecting a running order

To inspect the contents of a roCreate file, use the *mosromgr inspect* command:

```
$ mosromgr inspect -f 123456-roCreate.mos.xml
22:45 NEWSNIGHT 54D CORE Thu, 08.04.2021
```

Many options are available which allow for inspecting a file from an S3 bucket (-b and -k) instead of a local file (-f); and others which affect the output such as -t (start time), -d (duration), -s (stories):

```
$ mosromgr inspect -b my-bucket -k newsnight/20210804/123456-roCreate.mos.xml -tds
22:45 NEWSNIGHT 54D CORE Thu, 08.04.2021
Start time: 2021-04-08 21:46
Duration: 0:35:09

MENU START

MENU-PRE TITLE TEASE

MENU-TITLES

MENU-POST TITLE "ALSO TONIGHT"

NORTHERN IRELAND-INTRO

NORTHERN IRELAND-LEWIS PACKAGE

...
END OF PROGRAMME
```

Merging MOS files

To merge a set of MOS files for a programme, use the `mosromgr merge` command.

Merging local files:

```
$ mosromgr merge -f *.mos.xml -o FINAL.xml
...
INFO:mosromgr.moscollection:Merging RunningOrderEnd 123499
INFO:mosromgr.moscollection:Completed merging 99 mos files
Writing merged running order to FINAL.xml
```

Or files in an S3 bucket folder by prefix:

```
$ mosromgr merge -b my-bucket -p newsnight/20210101/ -o
...
INFO:mosromgr.moscollection:Merging RunningOrderEnd 123499
INFO:mosromgr.moscollection:Completed merging 99 mos files
Writing merged running order to FINAL.xml
```

2.4 API - MOS Types

This part of the module provides the classes required for classifying and managing MOS files.

MOS Type classes are typically imported like so:

```
from mosromgr.mostypes import MosFile
```

MOS objects are constructed using one of three classmethods. Either from a file path:

```
ro = RunningOrder.from_file('roCreate.mos.xml')
```

from an XML string:

```
with open('roCreate.mos.xml') as f:
    xml = f.read()

ro = RunningOrder.from_string(xml)
```

or from an S3 file key:

```
ro = RunningOrder.from_s3(bucket_name='newsnight', mos_file_key='20200101/roCreate.
➥mos.xml')
```

Similarly, objects constructed using these classmethods on the `MosFile` base class will be automatically classified and an instance of the relevant class will be created:

```
>>> ro = MosFile.from_file('roCreate.mos.xml')
>>> ro
<RunningOrder 1000>
>>> ss = MosFile.from_file('roStorySend.mos.xml')
>>> ss
<StorySend 1001>
>>> ro = MosFile.from_string(xml1)
>>> ro
<RunningOrder 1000>
```

(continues on next page)

(continued from previous page)

```
>>> ss = MosFile.from_string(xml2)
>>> ss
<StorySend 1001>
```

Even roElementAction files, which require a number of different subclasses, can be classified this way:

```
>>> ea1 = MosFile.from_file('roElementAction1.mos.xml')
>>> ea1
<EAStorySwap 1012>
>>> ea2 = MosFile.from_string(xml)
>>> ea2
<EAItemMove 1013>
```

2.4.1 MOS message classes

The following classes are used to parse and manage specific types of MOS messages.

RunningOrder

class mosromgr.mostypes.RunningOrder
 Bases: mosromgr.mostypes.MosFile

A RunningOrder object is created from a roCreate MOS file and can be constructed using classmethods `from_file()`, `from_string()` or `from_s3()`.

Specification: Create Running Order http://mosprotocol.com/wp-content/MOS-Protocol-Documents/MOSProtocolVersion40/index.html#calibre_link-32

__add__(other)

RunningOrder objects can be merged with other MOS files which implement a `merge` method by using the `+` operator, for example:

```
ro = RunningOrder.from_file('roCreate.mos.xml')
ss = StorySend.from_file('roStorySend.mos.xml')
ro += ss
```

__gt__(other)

Sort by `message_id` i.e. `ss > ro` or `sorted([ro, ss])`

__lt__(other)

Sort by `message_id` i.e. `ro < ss` or `sorted([ro, ss])`

__str__()

The XML string of the MOS file

classmethod from_file(mos_file_path)

Construct from a path to a MOS file

Parameters `mos_file_path(str)` – The MOS file path

classmethod from_s3(bucket_name, mos_file_key)

Construct from a MOS file in an S3 bucket

Parameters

- `bucket_name(str)` – The name of the S3 bucket
- `mos_file_key(str)` – A MOS file key within the S3 bucket

```
classmethod from_string(mos_xml_string)
    Construct from an XML string of a MOS document

    Parameters mos_xml_string(str) – The XML string of the MOS document

property base_tag
    The base tag (xml.etree.ElementTree.Element) within the xml, as determined by
    base_tag_name

property base_tag_name
    The name of the base XML tag for this file type (str)

property completed
    Whether or not the running order has had a RunningOrderEnd merged (bool)

property dict
    Convert XML to dictionary using xmltodict library. Useful for testing. (dict)

property duration
    Total running order duration in seconds (int)

property end_time
    Transmission end time (datetime.datetime)

property message_id
    The MOS file's message ID (int)

property ro_id
    The running order ID (str)

property ro_slug
    The running order slug (str)

property start_time
    Transmission start time (datetime.datetime)

property stories
    A list of Story objects within the running order

property xml
    The XML element of the MOS file (xml.etree.ElementTree.Element)
```

StorySend

```
class mosromgr.mostypes.StorySend
Bases: mosromgr.mostypes.MosFile
```

A StorySend object is created from a `roStorySend` MOS file and can be constructed using classmethods `from_file()`, `from_string()` or `from_s3()`.

StorySend objects can be merged with a `RunningOrder` by using the `+` operator. This behaviour is defined in the `merge()` method in this class.

Specification: Send Story information, including Body of the Story http://mosprotocol.com/wp-content/MOS-Protocol-Documents/MOSProtocolVersion40/index.html#calibre_link-49

```
__gt__(other)
    Sort by message_id i.e. ss > ro or sorted([ro, ss])

__lt__(other)
    Sort by message_id i.e. ro < ss or sorted([ro, ss])
```

```
__str__()
    The XML string of the MOS file

classmethod from_file(mos_file_path)
    Construct from a path to a MOS file

    Parameters mos_file_path(str) – The MOS file path

classmethod from_s3(bucket_name, mos_file_key)
    Construct from a MOS file in an S3 bucket

    Parameters
        • bucket_name(str) – The name of the S3 bucket
        • mos_file_key(str) – A MOS file key within the S3 bucket

classmethod from_string(mos_xml_string)
    Construct from an XML string of a MOS document

    Parameters mos_xml_string(str) – The XML string of the MOS document

merge(ro)
    Merge into the RunningOrder object provided.

    Replaces the story tag in the running order with the one in the roStorySend message.

property base_tag
    The base tag (xml.etree.ElementTree.Element) within the xml, as determined by base_tag_name

property base_tag_name
    The name of the base XML tag for this file type (str)

property dict
    Convert XML to dictionary using xmldict library. Useful for testing. (dict)

property message_id
    The MOS file's message ID (int)

property ro_id
    The running order ID (str)

property story
    The Story object being sent

property xml
    The XML element of the MOS file (xml.etree.ElementTree.Element)
```

StoryReplace

```
class mosromgr.mostypes.StoryReplace
Bases: mosromgr.mostypes.MosFile
```

A *StoryReplace* object is created from a *roStoryReplace* MOS file and can be constructed using class-methods `from_file()`, `from_string()` or `from_s3()`.

StoryReplace objects can be merged with a *RunningOrder* by using the + operator. This behaviour is defined in the `merge()` method in this class.

Specification: Replace a Story with Another in a Running Order http://mosprotocol.com/wp-content/MOS-Protocol-Documents/MOS_Protocol_Version_2.8.5_Final.htm#roStoryReplace

`__gt__(other)`
Sort by `message_id` i.e. `ss > ro` or `sorted([ro, ss])`

`__lt__(other)`
Sort by `message_id` i.e. `ro < ss` or `sorted([ro, ss])`

`__str__()`
The XML string of the MOS file

`classmethod from_file(mos_file_path)`
Construct from a path to a MOS file

Parameters `mos_file_path(str)` – The MOS file path

`classmethod from_s3(bucket_name, mos_file_key)`
Construct from a MOS file in an S3 bucket

Parameters

- `bucket_name(str)` – The name of the S3 bucket
- `mos_file_key(str)` – A MOS file key within the S3 bucket

`classmethod from_string(mos_xml_string)`
Construct from an XML string of a MOS document

Parameters `mos_xml_string(str)` – The XML string of the MOS document

`merge(ro)`
Merge into the `RunningOrder` object provided.

Replaces the story tag in the running order with the one in the `roStoryReplace` message.

`property base_tag`
The base tag (`xml.etree.ElementTree.Element`) within the `xml`, as determined by `base_tag_name`

`property base_tag_name`
The name of the base XML tag for this file type (`str`)

`property dict`
Convert XML to dictionary using `xmltodict` library. Useful for testing. (`dict`)

`property message_id`
The MOS file's message ID (`int`)

`property ro_id`
The running order ID (`str`)

`property source_story`
The replacement `Story` object

`property target_story`
The `Story` object being replaced

`property xml`
The XML element of the MOS file (`xml.etree.ElementTree.Element`)

StoryInsert

```
class mosromgr.mostypes.StoryInsert
Bases: mosromgr.mostypes.MosFile
```

A StoryInsert object is created from a roStoryInsert MOS file and can be constructed using class-methods `from_file()`, `from_string()` or `from_s3()`.

StoryInsert objects can be merged with a `RunningOrder` by using the + operator. This behaviour is defined in the `merge()` method in this class.

Specification: Insert Stories in Running Order http://mosprotocol.com/wp-content/MOS-Protocol-Documents/MOS_Protocol_Version_2.8.5_Final.htm#roStoryInsert

`__gt__(other)`

Sort by `message_id` i.e. `ss > ro` or `sorted([ro, ss])`

`__lt__(other)`

Sort by `message_id` i.e. `ro < ss` or `sorted([ro, ss])`

`__str__()`

The XML string of the MOS file

`classmethod from_file(mos_file_path)`

Construct from a path to a MOS file

Parameters `mos_file_path(str)` – The MOS file path

`classmethod from_s3(bucket_name, mos_file_key)`

Construct from a MOS file in an S3 bucket

Parameters

- `bucket_name(str)` – The name of the S3 bucket
- `mos_file_key(str)` – A MOS file key within the S3 bucket

`classmethod from_string(mos_xml_string)`

Construct from an XML string of a MOS document

Parameters `mos_xml_string(str)` – The XML string of the MOS document

`merge(ro)`

Merge into the `RunningOrder` object provided.

Inserts the story tags from the `roStoryInsert` message into the running order.

`property base_tag`

The base tag (`xml.etree.ElementTree.Element`) within the `xml`, as determined by `base_tag_name`

`property base_tag_name`

The name of the base XML tag for this file type (`str`)

`property dict`

Convert XML to dictionary using `xmldict` library. Useful for testing. (`dict`)

`property message_id`

The MOS file's message ID (`int`)

`property ro_id`

The running order ID (`str`)

`property source_stories`

A list of `Story` objects to be inserted

property target_story

The *Story* object above which the source stories are to be inserted

property xml

The XML element of the MOS file (`xml.etree.ElementTree.Element`)

StoryAppend**class mosromgr.mostypes.StoryAppend**

Bases: `mosromgr.mostypes.MosFile`

A StoryAppend object is created from a `roStoryAppend` MOS file and can be constructed using class-methods `from_file()`, `from_string()` or `from_s3()`.

StoryAppend objects can be merged with a `RunningOrder` by using the + operator. This behaviour is defined in the `merge()` method in this class.

Specification: Append Stories to Running Order http://mosprotocol.com/wp-content/MOS-Protocol-Documents/MOS_Protocol_Version_2.8.5_Final.htm#roStoryAppend

__gt__(other)

Sort by `message_id` i.e. `ss > ro` or `sorted([ro, ss])`

__lt__(other)

Sort by `message_id` i.e. `ro < ss` or `sorted([ro, ss])`

__str__()

The XML string of the MOS file

classmethod from_file(mos_file_path)

Construct from a path to a MOS file

Parameters `mos_file_path(str)` – The MOS file path

classmethod from_s3(bucket_name, mos_file_key)

Construct from a MOS file in an S3 bucket

Parameters

- `bucket_name(str)` – The name of the S3 bucket
- `mos_file_key(str)` – A MOS file key within the S3 bucket

classmethod from_string(mos_xml_string)

Construct from an XML string of a MOS document

Parameters `mos_xml_string(str)` – The XML string of the MOS document

merge(ro)

Merge into the `RunningOrder` object provided.

Adds the story tag in the `roStoryAppend` message onto the end of the running order.

property base_tag

The base tag (`xml.etree.ElementTree.Element`) within the `xml`, as determined by `base_tag_name`

property base_tag_name

The name of the base XML tag for this file type (`str`)

property dict

Convert XML to dictionary using `xmldict` library. Useful for testing. (`dict`)

```
property message_id
    The MOS file's message ID (int)

property ro_id
    The running order ID (str)

property stories
    A list of Story objects to be appended

property xml
    The XML element of the MOS file (xml.etree.ElementTree.Element)
```

StoryMove

```
class mosromgr.mostypes.StoryMove
Bases: mosromgr.mostypes.MosFile
```

A StoryMove object is created from a roStoryMove MOS file and can be constructed using classmethods `from_file()`, `from_string()` or `from_s3()`.

StoryMove objects can be merged with a `RunningOrder` by using the + operator. This behaviour is defined in the `merge()` method in this class.

Specification: Move a story to a new position in the Playlist http://mosprotocol.com/wp-content/MOS-Protocol-Documents/MOS_Protocol_Version_2.8.5_Final.htm#roStoryMove

```
__gt__(other)
    Sort by message_id i.e. ss > ro or sorted([ro, ss])
```

```
__lt__(other)
    Sort by message_id i.e. ro < ss or sorted([ro, ss])
```

```
__str__()
    The XML string of the MOS file
```

```
classmethod from_file(mos_file_path)
    Construct from a path to a MOS file
```

Parameters `mos_file_path(str)` – The MOS file path

```
classmethod from_s3(bucket_name, mos_file_key)
    Construct from a MOS file in an S3 bucket
```

Parameters

- `bucket_name(str)` – The name of the S3 bucket
- `mos_file_key(str)` – A MOS file key within the S3 bucket

```
classmethod from_string(mos_xml_string)
    Construct from an XML string of a MOS document
```

Parameters `mos_xml_string(str)` – The XML string of the MOS document

```
merge(ro)
    Merge into the RunningOrder object provided.
```

Moves the story given in the roStoryMove message to a new position in the running order.

```
property base_tag
```

The base tag (`xml.etree.ElementTree.Element`) within the `xml`, as determined by `base_tag_name`

```
property base_tag_name
    The name of the base XML tag for this file type (str)
property dict
    Convert XML to dictionary using xmldict library. Useful for testing. (dict)
property message_id
    The MOS file's message ID (int)
property ro_id
    The running order ID (str)
property source_story
    The Story object to be moved
property target_story
    The Story object above which the source story is to be moved
property xml
    The XML element of the MOS file (xml.etree.ElementTree.Element)
```

StoryDelete

```
class mosromgr.mostypes.StoryDelete
Bases: mosromgr.mostypes.MosFile
```

A StoryDelete object is created from a `roStoryDelete` MOS file and can be constructed using class-methods `from_file()`, `from_string()` or `from_s3()`.

StoryDelete objects can be merged with a `RunningOrder` by using the + operator. This behaviour is defined in the `merge()` method in this class.

Specification: Delete Stories from Running Order http://mosprotocol.com/wp-content/MOS-Protocol-Documents/MOS_Protocol_Version_2.8.5_Final.htm#roStoryDelete

__gt__(other)
Sort by `message_id` i.e. `ss > ro` or `sorted([ro, ss])`

__lt__(other)
Sort by `message_id` i.e. `ro < ss` or `sorted([ro, ss])`

__str__()
The XML string of the MOS file

classmethod from_file(mos_file_path)
Construct from a path to a MOS file

Parameters `mos_file_path(str)` – The MOS file path

classmethod from_s3(bucket_name, mos_file_key)
Construct from a MOS file in an S3 bucket

Parameters

- **bucket_name** (`str`) – The name of the S3 bucket
- **mos_file_key** (`str`) – A MOS file key within the S3 bucket

classmethod from_string(mos_xml_string)
Construct from an XML string of a MOS document

Parameters `mos_xml_string(str)` – The XML string of the MOS document

merge (ro)
Merge into the *RunningOrder* object provided.

Removes any story tags from the running order which are included in the *roStoryDelete* message.

property base_tag
The base tag (`xml.etree.ElementTree.Element`) within the `xml`, as determined by `base_tag_name`

property base_tag_name
The name of the base XML tag for this file type (`str`)

property dict
Convert XML to dictionary using `xmltodict` library. Useful for testing. (`dict`)

property message_id
The MOS file's message ID (`int`)

property ro_id
The running order ID (`str`)

property stories
A list of `Story` objects to be deleted

property xml
The XML element of the MOS file (`xml.etree.ElementTree.Element`)

MetaDataReplace

class mosromgr.mostypes.MetaDataReplace
Bases: `mosromgr.mostypes.MosFile`

A `MetaDataReplace` object is created from a `roMetadataReplace` MOS file and can be constructed using classmethods `from_file()`, `from_string()` or `from_s3()`.

`MetaDataReplace` objects can be merged with a *RunningOrder* by using the + operator. This behaviour is defined in the `merge()` method in this class.

Specification: Replace RO metadata without deleting the RO structure http://mosprotocol.com/wp-content/MOS-Protocol-Documents/MOSProtocolVersion40/index.html#calibre_link-34

__gt__(other)
Sort by `message_id` i.e. `ss > ro` or `sorted([ro, ss])`

__lt__(other)
Sort by `message_id` i.e. `ro < ss` or `sorted([ro, ss])`

__str__()
The XML string of the MOS file

classmethod from_file(mos_file_path)
Construct from a path to a MOS file

Parameters `mos_file_path (str)` – The MOS file path

classmethod from_s3(bucket_name, mos_file_key)
Construct from a MOS file in an S3 bucket

Parameters

- **bucket_name (str)** – The name of the S3 bucket
- **mos_file_key (str)** – A MOS file key within the S3 bucket

```
classmethod from_string(mos_xml_string)
Construct from an XML string of a MOS document

Parameters mos_xml_string(str) – The XML string of the MOS document

merge(ro)
Merge into the RunningOrder object provided.

Replaces the metadata tags in the running order with the ones in the MetaDataReplace message.

property base_tag
The base tag (xml.etree.ElementTree.Element) within the xml, as determined by base_tag_name

property base_tag_name
The name of the base XML tag for this file type (str)

property dict
Convert XML to dictionary using xmltodict library. Useful for testing. (dict)

property message_id
The MOS file's message ID (int)

property ro_id
The running order ID (str)

property ro_slug
The running order slug (str)

property xml
The XML element of the MOS file (xml.etree.ElementTree.Element)
```

ItemDelete

```
class mosromgr.mostypes.ItemDelete
Bases: mosromgr.mostypes.MosFile
```

An `ItemDelete` object is created from a `roItemDelete` MOS file and can be constructed using classmethods `from_file()`, `from_string()` or `from_s3()`.

`ItemDelete` objects can be merged with a `RunningOrder` by using the `+` operator. This behaviour is defined in the `merge()` method in this class.

Specification: Delete Items in Story http://mosprotocol.com/wp-content/MOS-Protocol-Documents/MOS_Protocol_Version_2.8.5_Final.htm#roItemDelete

```
__gt__(other)
Sort by message_id i.e. ss > ro or sorted([ro, ss])
```

```
__lt__(other)
Sort by message_id i.e. ro < ss or sorted([ro, ss])
```

```
__str__()
The XML string of the MOS file
```

```
classmethod from_file(mos_file_path)
Construct from a path to a MOS file
```

Parameters mos_file_path(str) – The MOS file path

```
classmethod from_s3(bucket_name, mos_file_key)
Construct from a MOS file in an S3 bucket
```

Parameters

- **bucket_name** (`str`) – The name of the S3 bucket
- **mos_file_key** (`str`) – A MOS file key within the S3 bucket

classmethod from_string(mos_xml_string)

Construct from an XML string of a MOS document

Parameters mos_xml_string(str) – The XML string of the MOS document

merge(ro)

Merge into the `RunningOrder` object provided.

Deletes any item tags with the IDs specified in the `roItemDelete` message from the running order.

property base_tag

The base tag (`xml.etree.ElementTree.Element`) within the `xml`, as determined by `base_tag_name`

property base_tag_name

The name of the base XML tag for this file type (`str`)

property dict

Convert XML to dictionary using `xmltodict` library. Useful for testing. (`dict`)

property message_id

The MOS file's message ID (`int`)

property ro_id

The running order ID (`str`)

property target_items

The `Item` objects being deleted

property target_story

The `Story` object containing the items being replaced

property xml

The XML element of the MOS file (`xml.etree.ElementTree.Element`)

ItemInsert

class mosromgr.mostypes.ItemInsert
Bases: `mosromgr.mostypes.MosFile`

An `ItemInsert` object is created from a `roItemInsert` MOS file and can be constructed using classmethods `from_file()`, `from_string()` or `from_s3()`.

`ItemInsert` objects can be merged with a `RunningOrder` by using the + operator. This behaviour is defined in the `merge()` method in this class.

Specification: Insert Items in Story http://mosprotocol.com/wp-content/MOS-Protocol-Documents/MOS_Protocol_Version_2.8.5_Final.htm#roItemInsert

__gt__(other)

Sort by `message_id`i.e. `ss > ro` or `sorted([ro, ss])`

__lt__(other)

Sort by `message_id`i.e. `ro < ss` or `sorted([ro, ss])`

__str__()

The XML string of the MOS file

```
classmethod from_file(mos_file_path)
    Construct from a path to a MOS file

    Parameters mos_file_path (str) – The MOS file path

classmethod from_s3(bucket_name, mos_file_key)
    Construct from a MOS file in an S3 bucket

    Parameters
        • bucket_name (str) – The name of the S3 bucket
        • mos_file_key (str) – A MOS file key within the S3 bucket

classmethod from_string(mos_xml_string)
    Construct from an XML string of a MOS document

    Parameters mos_xml_string (str) – The XML string of the MOS document

merge(ro)
    Merge into the RunningOrder object provided.

    Inserts the item tags from the roItemInsert message into the relevant story in the running order.

property base_tag
    The base tag (xml.etree.ElementTree.Element) within the xml, as determined by base_tag_name

property base_tag_name
    The name of the base XML tag for this file type (str)

property dict
    Convert XML to dictionary using xmltodict library. Useful for testing. (dict)

property message_id
    The MOS file's message ID (int)

property ro_id
    The running order ID (str)

property source_items
    A list of Item objects to be inserted

property target_item
    The Item object above which the source items will be inserted

property target_story
    The Story object into which the items are to be inserted

property xml
    The XML element of the MOS file (xml.etree.ElementTree.Element)
```

ItemMoveMultiple

```
class mosromgr.mostypes.ItemMoveMultiple
Bases: mosromgr.mostypes.MosFile
```

An `ItemMoveMultiple` object is created from a `roItemMoveMultiple` MOS file and can be constructed using classmethods `from_file()`, `from_string()` or `from_s3()`.

`ItemMoveMultiple` objects can be merged with a `RunningOrder` by using the `+` operator. This behaviour is defined in the `merge()` method in this class.

Specification: Move one or more Items to a specified position within a Story http://mosprotocol.com/wp-content/MOS-Protocol-Documents/MOS_Protocol_Version_2.8.5_Final.htm#roItemMoveMultiple

`__gt__(other)`

Sort by `message_id` i.e. `ss > ro` or `sorted([ro, ss])`

`__lt__(other)`

Sort by `message_id` i.e. `ro < ss` or `sorted([ro, ss])`

`__str__()`

The XML string of the MOS file

`classmethod from_file(mos_file_path)`

Construct from a path to a MOS file

Parameters `mos_file_path(str)` – The MOS file path

`classmethod from_s3(bucket_name, mos_file_key)`

Construct from a MOS file in an S3 bucket

Parameters

- **`bucket_name(str)`** – The name of the S3 bucket
- **`mos_file_key(str)`** – A MOS file key within the S3 bucket

`classmethod from_string(mos_xml_string)`

Construct from an XML string of a MOS document

Parameters `mos_xml_string(str)` – The XML string of the MOS document

`merge(ro)`

Merge into the `RunningOrder` object provided.

Moves item tags in the `roItemMove` message to a new position within the story.

`property base_tag`

The base tag (`xml.etree.ElementTree.Element`) within the `xml`, as determined by `base_tag_name`

`property base_tag_name`

The name of the base XML tag for this file type (`str`)

`property dict`

Convert XML to dictionary using `xmldict` library. Useful for testing. (`dict`)

`property message_id`

The MOS file's message ID (`int`)

`property ro_id`

The running order ID (`str`)

`property source_items`

A list of `Item` objects to be moved

`property target_item`

The `Item` object above which the source items will be moved

`property target_story`

The `Story` object containing the items being moved

`property xml`

The XML element of the MOS file (`xml.etree.ElementTree.Element`)

ItemReplace

```
class mosromgr.mostypes.ItemReplace
Bases: mosromgr.mostypes.MosFile
```

An ItemReplace object is created from a roItemReplace MOS file and can be constructed using class-methods `from_file()`, `from_string()` or `from_s3()`.

ItemReplace objects can be merged with a `RunningOrder` by using the + operator. This behaviour is defined in the `merge()` method in this class.

Specification: Replace an Item with one or more Items in a Story http://mosprotocol.com/wp-content/MOS-Protocol-Documents/MOS_Protocol_Version_2.8.5_Final.htm#roItemReplace

__gt__(other)

Sort by `message_id` i.e. `ss > ro` or `sorted([ro, ss])`

__lt__(other)

Sort by `message_id` i.e. `ro < ss` or `sorted([ro, ss])`

__str__()

The XML string of the MOS file

classmethod from_file(mos_file_path)

Construct from a path to a MOS file

Parameters `mos_file_path(str)` – The MOS file path

classmethod from_s3(bucket_name, mos_file_key)

Construct from a MOS file in an S3 bucket

Parameters

- `bucket_name(str)` – The name of the S3 bucket
- `mos_file_key(str)` – A MOS file key within the S3 bucket

classmethod from_string(mos_xml_string)

Construct from an XML string of a MOS document

Parameters `mos_xml_string(str)` – The XML string of the MOS document

merge(ro)

Merge into the `RunningOrder` object provided.

Replaces the story tag in the running order with the one in the `roStorySend` message

property base_tag

The base tag (`xml.etree.ElementTree.Element`) within the `xml`, as determined by `base_tag_name`

property base_tag_name

The name of the base XML tag for this file type (`str`)

property dict

Convert XML to dictionary using `xmltodict` library. Useful for testing. (`dict`)

property message_id

The MOS file's message ID (`int`)

property ro_id

The running order ID (`str`)

property source_items

A list of replacement `Item` objects

```
property target_item
    The Item object being replaced

property target_story
    The Story object containing the item being replaced

property xml
    The XML element of the MOS file (xml.etree.ElementTree.Element)
```

ReadyToAir

```
class mosromgr.mostypes.ReadyToAir
Bases: mosromgr.mostypes.MosFile
```

A ReadyToAir object is created from a `roReadyToAir` MOS file and can be constructed using classmethods `from_file()`, `from_string()` or `from_s3()`.

ReadyToAir objects can be merged with a `RunningOrder` by using the + operator. This behaviour is defined in the `merge()` method in this class.

Specification: Identify a Running Order as Ready to Air http://mosprotocol.com/wp-content/MOS-Protocol-Documents/MOSProtocolVersion40/index.html#calibre_link-41

```
__gt__(other)
    Sort by message_idi.e. ss > ro or sorted([ro, ss])
```

```
__lt__(other)
    Sort by message_idi.e. ro < ss or sorted([ro, ss])
```

```
__str__()
    The XML string of the MOS file
```

```
classmethod from_file(mos_file_path)
    Construct from a path to a MOS file
```

Parameters `mos_file_path(str)` – The MOS file path

```
classmethod from_s3(bucket_name, mos_file_key)
```

Construct from a MOS file in an S3 bucket

Parameters

- `bucket_name(str)` – The name of the S3 bucket
- `mos_file_key(str)` – A MOS file key within the S3 bucket

```
classmethod from_string(mos_xml_string)
```

Construct from an XML string of a MOS document

Parameters `mos_xml_string(str)` – The XML string of the MOS document

```
merge(ro)
```

Merge into the `RunningOrder` object provided.

Currently unimplemented - has no effect on the running order. TODO: #18

```
property base_tag
```

The base tag (`xml.etree.ElementTree.Element`) within the `xml`, as determined by `base_tag_name`

```
property base_tag_name
```

The name of the base XML tag for this file type (`str`)

```
property dict
    Convert XML to dictionary using xmldict library. Useful for testing. (dict)
property message_id
    The MOS file's message ID (int)
property ro_id
    The running order ID (str)
property xml
    The XML element of the MOS file (xml.etree.ElementTree.Element)
```

EAStoryReplace

```
class mosromgr.mostypes.EAStoryReplace
Bases: mosromgr.mostypes.ElementAction
```

An EAStoryReplace object is created from a roElementAction MOS file containing a story replacement, and can be constructed using classmethods `from_file()`, `from_string()` or `from_s3()`.

EAStoryReplace objects can be merged with a `RunningOrder` by using the + operator. This behaviour is defined in the `merge()` method in this class.

Specification: Replacing a story http://mosprotocol.com/wp-content/MOS-Protocol-Documents/MOSProtocolVersion40/index.html#calibre_link-43

```
__gt__(other)
    Sort by message_id i.e. ss > ro or sorted([ro, ss])
```

```
__lt__(other)
    Sort by message_id i.e. ro < ss or sorted([ro, ss])
```

```
__str__()
    The XML string of the MOS file
```

```
classmethod from_file(mos_file_path)
Construct from a path to a MOS file
```

Parameters `mos_file_path(str)` – The MOS file path

```
classmethod from_s3(bucket_name, mos_file_key)
Construct from a MOS file in an S3 bucket
```

Parameters

- `bucket_name(str)` – The name of the S3 bucket
- `mos_file_key(str)` – A MOS file key within the S3 bucket

```
classmethod from_string(mos_xml_string)
Construct from an XML string of a MOS document
```

Parameters `mos_xml_string(str)` – The XML string of the MOS document

```
merge(ro)
```

Merge into the `RunningOrder` object provided.

Replaces the `element_target` story tag in the running order with any story tags found in the `element_source` in the roElementAction message.

```
property base_tag
```

The base tag (`xml.etree.ElementTree.Element`) within the `xml`, as determined by `base_tag_name`

```
property base_tag_name
    The name of the base XML tag for this file type (str)
property dict
    Convert XML to dictionary using xmldict library. Useful for testing. (dict)
property message_id
    The MOS file's message ID (int)
property ro_id
    The running order ID (str)
property source_story
    The replacement Story object
property target_story
    The Story object being replaced
property xml
    The XML element of the MOS file (xml.etree.ElementTree.Element)
```

EAItemReplace

```
class mosromgr.mostypes.EAItemReplace
Bases: mosromgr.mostypes.ElementAction
```

An EAItemReplace object is created from a `roElementAction` MOS file containing an item replacement, and can be constructed using classmethods `from_file()`, `from_string()` or `from_s3()`.

EAItemReplace objects can be merged with a `RunningOrder` by using the + operator. This behaviour is defined in the `merge()` method in this class.

Specification: Replacing an item http://mosprotocol.com/wp-content/MOS-Protocol-Documents/MOSProtocolVersion40/index.html#calibre_link-43

```
__gt__(other)
    Sort by message_id i.e. ss > ro or sorted([ro, ss])
__lt__(other)
    Sort by message_id i.e. ro < ss or sorted([ro, ss])
__str__()
    The XML string of the MOS file
```

```
classmethod from_file(mos_file_path)
    Construct from a path to a MOS file
    Parameters mos_file_path (str) – The MOS file path
```

```
classmethod from_s3(bucket_name, mos_file_key)
    Construct from a MOS file in an S3 bucket
    Parameters
```

- `bucket_name` (`str`) – The name of the S3 bucket
- `mos_file_key` (`str`) – A MOS file key within the S3 bucket

```
classmethod from_string(mos_xml_string)
    Construct from an XML string of a MOS document
    Parameters mos_xml_string (str) – The XML string of the MOS document
```

merge (ro)
Merge into the *RunningOrder* object provided.
Replaces the target item tag in the target story in the running order with any item tags found in the `element_source` in the `roElementAction` message.

property base_tag
The base tag (`xml.etree.ElementTree.Element`) within the `xml`, as determined by `base_tag_name`

property base_tag_name
The name of the base XML tag for this file type (`str`)

property dict
Convert XML to dictionary using `xmldict` library. Useful for testing. (`dict`)

property message_id
The MOS file's message ID (`int`)

property ro_id
The running order ID (`str`)

property source_items
A list of replacement *Item* objects

property target_item
The *Item* object being replaced

property target_story
The *Story* object containing the item being replaced

property xml
The XML element of the MOS file (`xml.etree.ElementTree.Element`)

EAStoryDelete

class mosromgr.mostypes.EAStoryDelete

Bases: `mosromgr.mostypes.ElementAction`

An EAStoryDelete object is created from a `roElementAction` MOS file containing a story deletion, and can be constructed using classmethods `from_file()`, `from_string()` or `from_s3()`.

EAStoryDelete objects can be merged with a *RunningOrder* by using the + operator. This behaviour is defined in the `merge ()` method in this class.

Specification: Deleting stories http://mosprotocol.com/wp-content/MOS-Protocol-Documents/MOSProtocolVersion40/index.html#calibre_link-43

__gt__(other)
Sort by `message_id` i.e. `ss > ro` or `sorted([ro, ss])`

__lt__(other)
Sort by `message_id` i.e. `ro < ss` or `sorted([ro, ss])`

__str__()
The XML string of the MOS file

classmethod from_file(mos_file_path)
Construct from a path to a MOS file

Parameters `mos_file_path (str)` – The MOS file path

classmethod from_s3(bucket_name, mos_file_key)

Construct from a MOS file in an S3 bucket

Parameters

- **bucket_name** (*str*) – The name of the S3 bucket
- **mos_file_key** (*str*) – A MOS file key within the S3 bucket

classmethod from_string(mos_xml_string)

Construct from an XML string of a MOS document

Parameters mos_xml_string (*str*) – The XML string of the MOS document**merge(ro)**Merge into the *RunningOrder* object provided.

Removes any stories specified in element_source in the roElementAction message from the running order.

property base_tagThe base tag (`xml.etree.ElementTree.Element`) within the `xml`, as determined by `base_tag_name`**property base_tag_name**The name of the base XML tag for this file type (*str*)**property dict**Convert XML to dictionary using `xmltodict` library. Useful for testing. (*dict*)**property message_id**The MOS file's message ID (*int*)**property ro_id**The running order ID (*str*)**property stories**A list of *Story* objects to be deleted**property xml**The XML element of the MOS file (`xml.etree.ElementTree.Element`)

EAItemDelete

class mosromgr.mostypes.EAItemDeleteBases: `mosromgr.mostypes.ElementAction`An EAItemDelete object is created from a roElementAction MOS file containing an item deletion, and can be constructed using classmethods `from_file()`, `from_string()` or `from_s3()`.EAItemDelete objects can be merged with a *RunningOrder* by using the + operator. This behaviour is defined in the `merge()` method in this class.Specification: Deleting items http://mosprotocol.com/wp-content/MOS-Protocol-Documents/MOSProtocolVersion40/index.html#calibre_link-43**__gt__(other)**Sort by `message_id` i.e. `ss > ro` or `sorted([ro, ss])`**__lt__(other)**Sort by `message_id` i.e. `ro < ss` or `sorted([ro, ss])`

```
__str__()
    The XML string of the MOS file

classmethod from_file(mos_file_path)
    Construct from a path to a MOS file

    Parameters mos_file_path(str) – The MOS file path

classmethod from_s3(bucket_name, mos_file_key)
    Construct from a MOS file in an S3 bucket

    Parameters
        • bucket_name(str) – The name of the S3 bucket
        • mos_file_key(str) – A MOS file key within the S3 bucket

classmethod from_string(mos_xml_string)
    Construct from an XML string of a MOS document

    Parameters mos_xml_string(str) – The XML string of the MOS document

merge(ro)
    Merge into the RunningOrder object provided.

    Deletes any items specified in the element_target in the roStorySend message from the specified
    story in the running order.

property base_tag
    The base tag (xml.etree.ElementTree.Element) within the xml, as determined by
    base_tag_name

property base_tag_name
    The name of the base XML tag for this file type (str)

property dict
    Convert XML to dictionary using xmldict library. Useful for testing. (dict)

property message_id
    The MOS file's message ID (int)

property ro_id
    The running order ID (str)

property source_items
    A list of Item objects being deleted

property target_story
    The Story object containing the items being deleted

property xml
    The XML element of the MOS file (xml.etree.ElementTree.Element)
```

EASToryInsert

```
class mosromgr.mostypes.EASToryInsert
Bases: mosromgr.mostypes.ElementAction
```

An EASToryInsert object is created from a roElementAction MOS file containing a story insertion, and can be constructed using classmethods `from_file()`, `from_string()` or `from_s3()`.

EASToryInsert objects can be merged with a `RunningOrder` by using the + operator. This behaviour is defined in the `merge()` method in this class.

Specification: Inserting stories http://mosprotocol.com/wp-content/MOS-Protocol-Documents/MOSProtocolVersion40/index.html#calibre_link-43

`__gt__(other)`

Sort by `message_id` i.e. `ss > ro` or `sorted([ro, ss])`

`__lt__(other)`

Sort by `message_id` i.e. `ro < ss` or `sorted([ro, ss])`

`__str__()`

The XML string of the MOS file

`classmethod from_file(mos_file_path)`

Construct from a path to a MOS file

Parameters `mos_file_path(str)` – The MOS file path

`classmethod from_s3(bucket_name, mos_file_key)`

Construct from a MOS file in an S3 bucket

Parameters

- `bucket_name(str)` – The name of the S3 bucket
- `mos_file_key(str)` – A MOS file key within the S3 bucket

`classmethod from_string(mos_xml_string)`

Construct from an XML string of a MOS document

Parameters `mos_xml_string(str)` – The XML string of the MOS document

`merge(ro)`

Merge into the `RunningOrder` object provided.

Inserts any story tags found in the `element_source` in the `roElementAction` message into the running order.

`property base_tag`

The base tag (`xml.etree.ElementTree.Element`) within the `xml`, as determined by `base_tag_name`

`property base_tag_name`

The name of the base XML tag for this file type (`str`)

`property dict`

Convert XML to dictionary using `xmldict` library. Useful for testing. (`dict`)

`property message_id`

The MOS file's message ID (`int`)

`property ro_id`

The running order ID (`str`)

property source_stories
The *Story* objects to be inserted

property target_story
The *Story* object above which the source story will be inserted

property xml
The XML element of the MOS file (`xml.etree.ElementTree.Element`)

EAItemInsert

class mosromgr.mostypes.EAItemInsert
Bases: `mosromgr.mostypes.ElementAction`

An EAItemInsert object is created from a roElementAction MOS file containing an item insertion, and can be constructed using classmethods `from_file()`, `from_string()` or `from_s3()`.

EAItemInsert objects can be merged with a *RunningOrder* by using the + operator. This behaviour is defined in the `merge()` method in this class.

Specification: *Inserting items* http://mosprotocol.com/wp-content/MOS-Protocol-Documents/MOSProtocolVersion40/index.html#calibre_link-43

__gt__(other)
Sort by `message_id`i.e. `ss > ro` or `sorted([ro, ss])`

__lt__(other)
Sort by `message_id`i.e. `ro < ss` or `sorted([ro, ss])`

__str__()
The XML string of the MOS file

classmethod from_file(mos_file_path)
Construct from a path to a MOS file

Parameters `mos_file_path(str)` – The MOS file path

classmethod from_s3(bucket_name, mos_file_key)
Construct from a MOS file in an S3 bucket

Parameters

- `bucket_name(str)` – The name of the S3 bucket
- `mos_file_key(str)` – A MOS file key within the S3 bucket

classmethod from_string(mos_xml_string)
Construct from an XML string of a MOS document

Parameters `mos_xml_string(str)` – The XML string of the MOS document

merge(ro)
Merge into the *RunningOrder* object provided.

Inserts any item tags found in the `element_source` in the roElementAction message into the relevant story in the running order.

property base_tag
The base tag (`xml.etree.ElementTree.Element`) within the `xml`, as determined by `base_tag_name`

property base_tag_name
The name of the base XML tag for this file type (`str`)

```
property dict
    Convert XML to dictionary using xmllib library. Useful for testing. (dict)
property message_id
    The MOS file's message ID (int)
property ro_id
    The running order ID (str)
property source_items
    A list of Item objects to be inserted
property target_item
    The Item object above which the source item is to be inserted
property target_story
    The Story object into which the item is to be inserted
property xml
    The XML element of the MOS file (xml.etree.ElementTree.Element)
```

EAStorySwap

```
class mosromgr.mostypes.EAStorySwap
Bases: mosromgr.mostypes.ElementAction
```

An EAStorySwap object is created from a `roElementAction` MOS file containing a story swap, and can be constructed using classmethods `from_file()`, `from_string()` or `from_s3()`.

EAStorySwap objects can be merged with a `RunningOrder` by using the + operator. This behaviour is defined in the `merge()` method in this class.

Specification: *Swapping stories* http://mosprotocol.com/wp-content/MOS-Protocol-Documents/MOSProtocolVersion40/index.html#calibre_link-43

```
__gt__(other)
    Sort by message_id i.e. ss > ro or sorted([ro, ss])
__lt__(other)
    Sort by message_id i.e. ro < ss or sorted([ro, ss])
__str__()
    The XML string of the MOS file
```

```
classmethod from_file(mos_file_path)
Construct from a path to a MOS file

    Parameters mos_file_path(str) – The MOS file path
```

```
classmethod from_s3(bucket_name, mos_file_key)
Construct from a MOS file in an S3 bucket
```

Parameters

- `bucket_name(str)` – The name of the S3 bucket
- `mos_file_key(str)` – A MOS file key within the S3 bucket

```
classmethod from_string(mos_xml_string)
Construct from an XML string of a MOS document
```

```
    Parameters mos_xml_string(str) – The XML string of the MOS document
```

merge (ro)
Merge into the *RunningOrder* object provided.

Swaps the order of the two story tags specified in `element_source` in the `roElementAction` message in the running order.

property base_tag
The base tag (`xml.etree.ElementTree.Element`) within the `xml`, as determined by `base_tag_name`

property base_tag_name
The name of the base XML tag for this file type (`str`)

property dict
Convert XML to dictionary using `xmldict` library. Useful for testing. (`dict`)

property message_id
The MOS file's message ID (`int`)

property ro_id
The running order ID (`str`)

property stories
A set of the two `Story` objects to be swapped

property xml
The XML element of the MOS file (`xml.etree.ElementTree.Element`)

EAltemSwap

class mosromgr.mostypes.EAltemSwap
Bases: `mosromgr.mostypes.ElementAction`

An EAltemSwap object is created from a `roElementAction` MOS file containing an item swap, and can be constructed using classmethods `from_file()`, `from_string()` or `from_s3()`.

EAltemSwap objects can be merged with a `RunningOrder` by using the + operator. This behaviour is defined in the `merge ()` method in this class.

Specification: Swapping items http://mosprotocol.com/wp-content/MOS-Protocol-Documents/MOSProtocolVersion40/index.html#calibre_link-43

__gt__ (other)
Sort by `message_id` i.e. `ss > ro` or `sorted([ro, ss])`

__lt__ (other)
Sort by `message_id` i.e. `ro < ss` or `sorted([ro, ss])`

__str__ ()
The XML string of the MOS file

classmethod from_file (mos_file_path)
Construct from a path to a MOS file

Parameters `mos_file_path (str)` – The MOS file path

classmethod from_s3 (bucket_name, mos_file_key)
Construct from a MOS file in an S3 bucket

Parameters

- `bucket_name (str)` – The name of the S3 bucket

- **mos_file_key** (*str*) – A MOS file key within the S3 bucket

classmethod from_string (*mos_xml_string*)
Construct from an XML string of a MOS document

Parameters **mos_xml_string** (*str*) – The XML string of the MOS document

merge (*ro*)
Merge into the *RunningOrder* object provided.

Swaps the order of the two item tags specified in `element_source` in the `roElementAction` message in the relevant story in the running order.

property base_tag
The base tag (`xml.etree.ElementTree.Element`) within the `xml`, as determined by `base_tag_name`

property base_tag_name
The name of the base XML tag for this file type (*str*)

property dict
Convert XML to dictionary using `xmldict` library. Useful for testing. (*dict*)

property message_id
The MOS file's message ID (*int*)

property ro_id
The running order ID (*str*)

property source_items
A set of *Item* objects to be swapped

property target_story
The *Story* object containing the items being swapped

property xml
The XML element of the MOS file (`xml.etree.ElementTree.Element`)

EASToryMove

class `mosromgr.mostypes.EASToryMove`
Bases: `mosromgr.mostypes.ElementAction`

An EASToryMove object is created from a `roElementAction` MOS file containing a story move, and can be constructed using classmethods `from_file()`, `from_string()` or `from_s3()`.

EASToryMove objects can be merged with a *RunningOrder* by using the + operator. This behaviour is defined in the `merge()` method in this class.

Specification: Moving stories http://mosprotocol.com/wp-content/MOS-Protocol-Documents/MOSProtocolVersion40/index.html#calibre_link-43

__gt__(other)
Sort by `message_id` i.e. `ss > ro` or `sorted([ro, ss])`

__lt__(other)
Sort by `message_id` i.e. `ro < ss` or `sorted([ro, ss])`

__str__()
The XML string of the MOS file

classmethod from_file (*mos_file_path*)
Construct from a path to a MOS file

Parameters `mos_file_path` (`str`) – The MOS file path

classmethod `from_s3` (`bucket_name, mos_file_key`)
Construct from a MOS file in an S3 bucket

Parameters

- `bucket_name` (`str`) – The name of the S3 bucket
- `mos_file_key` (`str`) – A MOS file key within the S3 bucket

classmethod `from_string` (`mos_xml_string`)
Construct from an XML string of a MOS document

Parameters `mos_xml_string` (`str`) – The XML string of the MOS document

merge (`ro`)
Merge into the `RunningOrder` object provided.

Moves story tags in `element_source` to the specified location in the running order.

property base_tag
The base tag (`xml.etree.ElementTree.Element`) within the `xml`, as determined by `base_tag_name`

property base_tag_name
The name of the base XML tag for this file type (`str`)

property dict
Convert XML to dictionary using `xmldict` library. Useful for testing. (`dict`)

property message_id
The MOS file's message ID (`int`)

property ro_id
The running order ID (`str`)

property source_stories
A list of replacement `Story` objects

property target_story
The `Story` object being replaced

property xml
The XML element of the MOS file (`xml.etree.ElementTree.Element`)

EAItemMove

```
class mosromgr.mostypes.EAItemMove
Bases: mosromgr.mostypes.ElementAction
```

An EAItemMove object is created from a `roElementAction` MOS file containing an item move, and can be constructed using classmethods `from_file()`, `from_string()` or `from_s3()`.

EAItemMove objects can be merged with a `RunningOrder` by using the + operator. This behaviour is defined in the `merge()` method in this class.

Specification: Moving items http://mosprotocol.com/wp-content/MOS-Protocol-Documents/MOSProtocolVersion40/index.html#calibre_link-43

```
__gt__ (other)
Sort by message_id i.e. ss > ro or sorted([ro, ss])
```

__lt__(other)
Sort by `message_id` i.e. `ro < ss` or `sorted([ro, ss])`

__str__()
The XML string of the MOS file

classmethod from_file(mos_file_path)
Construct from a path to a MOS file

Parameters `mos_file_path(str)` – The MOS file path

classmethod from_s3(bucket_name, mos_file_key)
Construct from a MOS file in an S3 bucket

Parameters

- `bucket_name(str)` – The name of the S3 bucket
- `mos_file_key(str)` – A MOS file key within the S3 bucket

classmethod from_string(mos_xml_string)
Construct from an XML string of a MOS document

Parameters `mos_xml_string(str)` – The XML string of the MOS document

merge(ro)

Merge into the `RunningOrder` object provided.

Moves item tags in `element_source` to the specified location in the story in the running order.

property base_tag

The base tag (`xml.etree.ElementTree.Element`) within the `xml`, as determined by `base_tag_name`

property base_tag_name

The name of the base XML tag for this file type (`str`)

property dict

Convert XML to dictionary using `xmltodict` library. Useful for testing. (`dict`)

property message_id

The MOS file's message ID (`int`)

property ro_id

The running order ID (`str`)

property source_item

The `Item` object to be moved

property target_items

A list of `Item` object above which the source items will be moved

property target_story

The `Story` object containing the item being replaced

property xml

The XML element of the MOS file (`xml.etree.ElementTree.Element`)

RunningOrderReplace

class mosromgr.mostypes.RunningOrderReplace
Bases: `mosromgr.mostypes.RunningOrder`

An RunningOrderReplace object is created from a roReplace MOS file and can be constructed using classmethods `from_file()`, `from_string()` or `from_s3()`.

RunningOrderReplace objects can be merged with a `RunningOrder` by using the + operator. This behaviour is defined in the `merge()` method in this class.

Specification: Replace Running Order http://mosprotocol.com/wp-content/MOS-Protocol-Documents/MOSProtocolVersion40/index.html#calibre_link-33

__add__(other)

RunningOrder objects can be merged with other MOS files which implement a merge method by using the + operator, for example:

```
ro = RunningOrder.from_file('roCreate.mos.xml')
ss = StorySend.from_file('roStorySend.mos.xml')
ro += ss
```

__gt__(other)

Sort by `message_id` i.e. `ss > ro` or `sorted([ro, ss])`

__lt__(other)

Sort by `message_id` i.e. `ro < ss` or `sorted([ro, ss])`

__str__()

The XML string of the MOS file

classmethod from_file(mos_file_path)

Construct from a path to a MOS file

Parameters `mos_file_path(str)` – The MOS file path

classmethod from_s3(bucket_name, mos_file_key)

Construct from a MOS file in an S3 bucket

Parameters

- `bucket_name(str)` – The name of the S3 bucket
- `mos_file_key(str)` – A MOS file key within the S3 bucket

classmethod from_string(mos_xml_string)

Construct from an XML string of a MOS document

Parameters `mos_xml_string(str)` – The XML string of the MOS document

merge(ro)

Merge into the `RunningOrder` object provided.

Replaces the entire `roCreate` tag in the running order with the one in the `roReplace` message.

property base_tag

The base tag (`xml.etree.ElementTree.Element`) within the `xml`, as determined by `base_tag_name`

property base_tag_name

The name of the base XML tag for this file type (`str`)

property dict

Convert XML to dictionary using `xmldict` library. Useful for testing. (`dict`)

```
property duration
    Total running order duration in seconds (int)

property end_time
    Transmission end time (datetime.datetime)

property message_id
    The MOS file's message ID (int)

property ro_id
    The running order ID (str)

property ro_slug
    The running order slug (str)

property start_time
    Transmission start time (datetime.datetime)

property stories
    A list of Story objects within the running order

property xml
    The XML element of the MOS file (xml.etree.ElementTree.Element)
```

RunningOrderEnd

```
class mosromgr.mostypes.RunningOrderEnd
Bases: mosromgr.mostypes.MosFile
```

A RunningOrderEnd object is created from a roDelete MOS file and can be constructed using classmethods *from_file()*, *from_string()* or *from_s3()*.

RunningOrderEnd objects can be merged with a *RunningOrder* by using the + operator. This behaviour is defined in the *merge()* method in this class. Once a RunningOrderEnd object has been merged into a *RunningOrder*, the running order is considered “completed” and no further messages can be merged (with the exception of *RunningOrderControl*).

Specification: Delete Running Order http://mosprotocol.com/wp-content/MOS-Protocol-Documents/MOSProtocolVersion40/index.html#calibre_link-35

```
__gt__(other)
    Sort by message_id i.e. ss > ro or sorted([ro, ss])
```

```
__lt__(other)
    Sort by message_id i.e. ro < ss or sorted([ro, ss])
```

```
__str__()
    The XML string of the MOS file
```

```
classmethod from_file(mos_file_path)
    Construct from a path to a MOS file
```

Parameters **mos_file_path** (*str*) – The MOS file path

```
classmethod from_s3(bucket_name, mos_file_key)
    Construct from a MOS file in an S3 bucket
```

Parameters

- **bucket_name** (*str*) – The name of the S3 bucket
- **mos_file_key** (*str*) – A MOS file key within the S3 bucket

```
classmethod from_string(mos_xml_string)
Construct from an XML string of a MOS document

Parameters mos_xml_string(str) – The XML string of the MOS document

merge(ro)
Merge into the RunningOrder object provided.

Adds a mosromgrmeta tag containing the roDelete tag from the roDelete message to the roCreate tag in the running order.

property base_tag
The base tag (xml.etree.ElementTree.Element) within the xml, as determined by base_tag_name

property base_tag_name
The name of the base XML tag for this file type (str)

property dict
Convert XML to dictionary using xmltodict library. Useful for testing. (dict)

property message_id
The MOS file's message ID (int)

property ro_id
The running order ID (str)

property xml
The XML element of the MOS file (xml.etree.ElementTree.Element)
```

RunningOrderControl

```
class mosromgr.mostypes.RunningOrderControl
Bases: mosromgr.mostypes.MosFile

A RunningOrderControl object is created from a roCtrl MOS file and can be constructed using class-methods from_file(), from_string() or from_s3().

Specification: Running Order Control http://mosprotocol.com/wp-content/MOS-Protocol-Documents/MOSProtocolVersion40/index.html#calibre\_link-47

TODO: generalise this class #20

__gt__(other)
Sort by message_id i.e. ss > ro or sorted([ro, ss])

__lt__(other)
Sort by message_id i.e. ro < ss or sorted([ro, ss])

__str__()
The XML string of the MOS file

classmethod from_file(mos_file_path)
Construct from a path to a MOS file

Parameters mos_file_path(str) – The MOS file path

classmethod from_s3(bucket_name, mos_file_key)
Construct from a MOS file in an S3 bucket
```

Parameters

- **bucket_name(str)** – The name of the S3 bucket

- **mos_file_key** (`str`) – A MOS file key within the S3 bucket

classmethod from_string (`mos_xml_string`)
Construct from an XML string of a MOS document

Parameters `mos_xml_string` (`str`) – The XML string of the MOS document

merge (`ro`)
Merge into the `RunningOrder` object provided.

Replaces the story tag in the running order with the one in the `roStorySend` message

property base_tag
The base tag (`xml.etree.ElementTree.Element`) within the `xml`, as determined by `base_tag_name`

property base_tag_name
The name of the base XML tag for this file type (`str`)

property dict
Convert XML to dictionary using `xmldict` library. Useful for testing. (`dict`)

property message_id
The MOS file's message ID (`int`)


property ro_id
The running order ID (`str`)

property story
The story to which this `roCtrl` message relates

property xml
The XML element of the MOS file (`xml.etree.ElementTree.Element`)

2.4.2 Base classes

Since some logic is shared between MOS file management, some inheritance is used in the implementation:



MosFile

```
class mosromgr.mostypes.MosFile
    Base class for all MOS files

    classmethod from_file(mos_file_path)
        Construct from a path to a MOS file

        Parameters mos_file_path (str) – The MOS file path

    classmethod from_s3(bucket_name, mos_file_key)
        Construct from a MOS file in an S3 bucket

        Parameters
            • bucket_name (str) – The name of the S3 bucket
            • mos_file_key (str) – A MOS file key within the S3 bucket

    classmethod from_string(mos_xml_string)
        Construct from an XML string of a MOS document

        Parameters mos_xml_string (str) – The XML string of the MOS document

    property base_tag
        The base tag (xml.etree.ElementTree.Element) within the xml, as determined by
        base_tag_name

    property base_tag_name
        The base tag (xml.etree.ElementTree.Element) within the xml, as determined by
        base_tag_name

    property dict
        Convert XML to dictionary using xmldict library. Useful for testing. (dict)

    property message_id
        The MOS file's message ID (int)

    property ro_id
        The running order ID (str)

    property xml
        The XML element of the MOS file (xml.etree.ElementTree.Element)
```

ElementAction

```
class mosromgr.mostypes.ElementAction
    Base class for various roElementAction MOS files

    classmethod from_file(mos_file_path)
        Construct from a path to a MOS file

        Parameters mos_file_path (str) – The MOS file path

    classmethod from_s3(bucket_name, mos_file_key)
        Construct from a MOS file in an S3 bucket

        Parameters
            • bucket_name (str) – The name of the S3 bucket
            • mos_file_key (str) – A MOS file key within the S3 bucket
```

```
classmethod from_string(mos_xml_string)
    Construct from an XML string of a MOS document

    Parameters mos_xml_string (str) – The XML string of the MOS document

property base_tag
    The base tag (xml.etree.ElementTree.Element) within the xml, as determined by base_tag_name

property base_tag_name
    The name of the base XML tag for this file type (str)

property dict
    Convert XML to dictionary using xmltodict library. Useful for testing. (dict)

property message_id
    The MOS file's message ID (int)

property ro_id
    The running order ID (str)

property xml
    The XML element of the MOS file (xml.etree.ElementTree.Element)
```

2.5 API - MOS Elements

This part of the module provides a collection of classes used to provide easy access to certain elements within a `MosFile` object, such as a list of stories within a running order, and the items within a story.

Although usually not required directly, the MOS Element classes can be imported as follows:

```
from mosromgr.moselements import Story
```

2.5.1 Element classes

Story

```
class mosromgr.moselements.Story
Bases: mosromgr.moselements.MosElement
```

This class represents a Story element within any `MosFile` object, providing data relating to the story. The Story ID, Story slug, duration and more are exposed as properties, and the parent XML element is provided for further introspection.

```
__str__()
    The XML string

property duration
    The story duration (the sum of the text time and media time found within
    mosExternalMetadata->mosPayload), in seconds (float)

property end_time
    The transmission end time of the story (datetime.datetime or None if not available in the XML)

property id
    The Story ID (str)
```

property items

List of `Item` elements found within the story (can be `None` if not available in the XML)

property offset

The time offset of the story in seconds (`float` or `None` if not available in the XML)

property slug

The Story slug (`str` or `None` if not available in the XML)

property start_time

The transmission start time of the story (`datetime.datetime` or `None` if not available in the XML)

property xml

The parent XML element (`xml.etree.ElementTree.Element`)

Item**class mosromgr.moselements.Item**

Bases: `mosromgr.moselements.MosElement`

This class represents an Item element within any `MosFile` object, providing data relating to the item within a `Story`. The Item ID and Item slug are exposed as properties, and the parent XML element is provided for further introspection.

__str__()

The XML string

property id

The Item ID (`str`)

property note

The item note text (`str` or `None` if not found)

property slug

The Item slug (`str` or `None` if not available in the XML)

property xml

The parent XML element (`xml.etree.ElementTree.Element`)

2.5.2 Base classes

MosElement**class mosromgr.moselements.MosElement**

Abstract base class for MOS elements

__str__()

The XML string

property id

The element ID (`str`)

property slug

The element slug (`str` or `None` if not available in the XML)

property xml

The parent XML element (`xml.etree.ElementTree.Element`)

2.6 API - MOS Collection

This part of the module provides a wrapper class `MosCollection` which stores references to specified MOS files, strings or S3 object keys so the `MosFile` objects can be recreated when needed rather than kept in memory.

Note: Note that creating a `MosCollection` from strings does not benefit from memory efficiency as the strings would still be held in memory.

The `MosCollection` is typically imported like so:

```
from mosromgr.moscollection import MosCollection
```

MOS collections are constructed using one of three classmethods. Either from a list of file paths:

```
mos_files = ['roCreate.mos.xml', 'roStorySend.mos.xml', 'roDelete.mos.xml']
mc = MosCollection.from_files(mos_files)
```

from a list of strings:

```
mos_strings = [roCreate, roStorySend, roDelete]
mc = MosCollection.from_strings(mos_files)
```

or from an S3 bucket:

```
mc = MosCollection.from_s3(bucket_name=bucket_name, prefix=prefix)
```

2.6.1 MosCollection

`class mosromgr.moscollection.MosCollection`

Wrapper for a collection of MOS files representing a partial or complete programme

`__str__()`

The XML string of the collection's running order

`classmethod from_files(mos_file_paths, *, allow_incomplete=False)`

Construct from a list of MOS file paths

Parameters

- `mos_file_paths (list)` – A list of paths to MOS files
- `allow_incomplete (bool)` – If False (the default), the collection is permitted to be constructed without a `roDelete`. If True, a `InvalidMosCollection` will be raised if one is not present. (keyword-only argument)

`classmethod from_s3(*, bucket_name, prefix, suffix='.mos.xml', allow_incomplete=False)`

Construct from a list of MOS files in an S3 bucket

Parameters

- `bucket_name (str)` – The name of the S3 bucket (keyword-only argument)
- `prefix (str)` – The prefix of the file keys in the S3 bucket (keyword-only argument)
- `suffix (str)` – The suffix of the file keys in the S3 bucket (keyword-only argument). Defaults to ‘.mos.xml’.

- **allow_incomplete** (`bool`) – If True, the collection is permitted to be constructed without a `roDelete`. If False (the default), a `InvalidMosCollection` will be raised if one is not present. (keyword-only argument)

```
classmethod from_strings(mos_file_strings, *, allow_incomplete=False)
Construct from a list of MOS document XML strings
```

Parameters

- **mos_file_paths** (`list`) – A list of paths to MOS files
- **allow_incomplete** (`bool`) – If False (the default), the collection is permitted to be constructed without a `roDelete`. If True, a `InvalidMosCollection` will be raised if one is not present. (keyword-only argument)

```
merge()
```

Merge all MOS files into the collection's running order (`ro`)

```
property completed
```

Whether or not the running order has had a `RunningOrderEnd` merged (`bool`)

```
property mos_readers
```

A list of `MosReader` objects representing all MOS files in the collection, except the `RunningOrder` (`roCreate`) which is held in `ro`

```
property ro
```

The collection's `RunningOrder` object

```
property ro_id
```

The running order ID

```
property ro_slug
```

The running order slug

2.6.2 MosReader

The `MosReader` class is internal and is not intended to be constructed by the user. A `MosCollection` object will contain a list of `MosReader` instances, so users may find it useful to refer to its members.

```
class mosromgr.moscollection.MosReader
```

Internal construct for opening and inspecting a MOS file for the purposes of classifying, sorting and validating a `MosCollection`. Provides the means to reconstruct the `MosFile` instance when needed in order to preserve memory usage.

```
property message_id
```

The message ID of the MOS file (`str`)

```
property mos_object
```

Restore the MOS object and return it (`MosFile`)

```
property mos_type
```

The `MosFile` subclass this object was classified as (returns the class object, not an instance or a string)

```
property ro_id
```

The MOS file's running order ID (`str`)

2.7 API - Utilities

This part of the module provides a collection of generic utilities which are largely for internal use.

The various utilities are typically imported like so:

```
from mosromgr.utils import s3
```

Warning: This part of the module should not be considered part of the stable API and is subject to backwards-incompatible changes.

2.7.1 S3

AWS S3 utilities

`get_mos_files`

```
mosromgr.utils.s3.get_mos_files(bucket_name, prefix=None, *, suffix='.mos.xml')
```

Retrieve MOS files from given S3 bucket in location defined by *prefix*. Returns a list of file keys.

`get_file_contents`

```
mosromgr.utils.s3.get_file_contents(bucket_name, file_key)
```

Open the S3 file and return its contents as a string

2.7.2 XML

XML helper functions

`remove_node`

```
mosromgr.utils.xml.remove_node(parent, node)
```

Remove *node* from *parent*.

`replace_node`

```
mosromgr.utils.xml.replace_node(parent, old_node, new_node, index)
```

Replace *old_node* with *new_node* in *parent* at *index*.

insert_node

```
mosromgr.utils.xml.insert_node(parent, node, index)  
    Insert node in parent at index.
```

find_child

```
mosromgr.utils.xml.find_child(parent, child_tag, id=None)  
    Find an element with child_tag in parent and return (child, index) or (None, None) if not found. If  
    id is provided, it will be searched for, otherwise the first child will be returned.
```

2.8 API - Exceptions

The module's exceptions and warnings are typically imported like so:

```
from mosromgr.exc import MosRoMgrException
```

The library's base warning is *MosRoMgrWarning* and others are detailed below.

2.8.1 Errors

MosRoMgrException

```
exception mosromgr.exc.MosRoMgrException  
    Bases: Exception  
  
    Base class for all mosromgr exceptions
```

UnknownMosFileType

```
exception mosromgr.exc.UnknownMosFileType  
    Bases: mosromgr.exc.MosRoMgrException  
  
    Exception raised when a MOS file type cannot be determined
```

MosMergeError

```
exception mosromgr.exc.MosMergeError  
    Bases: mosromgr.exc.MosRoMgrException  
  
    Exception raised when MOS merge fails
```

MosCompletedMergeError

```
exception mosromgr.exc.MosCompletedMergeError
Bases: mosromgr.exc.MosMergeError
```

Exception raised when MOS merge is attempted on a completed *RunningOrder*

InvalidMosCollection

```
exception mosromgr.exc.InvalidMosCollection
Bases: mosromgr.exc.MosRoMgrException
```

Exception raised when MosCollection fails validation

MosInvalidXML

```
exception mosromgr.exc.MosInvalidXML
Bases: mosromgr.exc.MosRoMgrException
```

Exception raised when *MosFile* cannot parse given XML

2.8.2 Warnings

MosRoMgrWarning

```
exception mosromgr.exc.MosRoMgrWarning
Bases: Warning
```

Base class for all warnings in mosromgr

ItemNotFoundWarning

```
exception mosromgr.exc.ItemNotFoundWarning
Bases: mosromgr.exc.MosRoMgrWarning
```

Warning raised when an item cannot be found during a *MosFile* merge

StoryNotFoundWarning

```
exception mosromgr.exc.StoryNotFoundWarning
Bases: mosromgr.exc.MosRoMgrWarning
```

Warning raised when a story cannot be found during a *MosFile* merge

DuplicateStoryWarning

```
exception mosromgr.exc.DuplicateStoryWarning
Bases: mosromgr.exc.MosRomgrWarning
```

Warning raised when a story being added is already found during a `EAStoryInsert` merge

2.9 Command line interface

This section lists the module's command line commands and provides a reference to their arguments. For examples, see the *Using the command line interface* section.

2.9.1 mosromgr

```
usage: mosromgr [-h] [--version] {help,detect,inspect,merge} ...

mosromgr is a tool for managing MOS running orders

optional arguments:
  -h, --help            show this help message and exit
  --version           show program's version number and exit

commands:
  {help,detect,inspect,merge}
    help                  Displays help about the specified command
    detect                Detect the MOS type of one or more files
    inspect              Inspect the contents of a roCreate file
    merge                Merge the provided MOS files
```

2.9.2 mosromgr detect

```
usage: mosromgr detect [-h] [-f [files [files ...]]] [-b bucket] [-p prefix] [-s suffix] [-k key]

Detect the MOS type of one or more files

optional arguments:
  -h, --help            show this help message and exit
  -f [files [files ...]], --files [files [files ...]]
                        The MOS files to detect
  -b bucket, --bucket-name bucket
                        S3 bucket name containing the MOS files
  -p prefix, --prefix prefix
                        The prefix for MOS files in the S3 bucket
  -s suffix, --suffix suffix
                        The suffix for MOS files in the S3 bucket
  -k key, --key key     The file key for a MOS file in the S3 bucket
```

2.9.3 mosromgr inspect

```
usage: mosromgr inspect [-h] [-f file] [-b bucket] [-k key] [-t] [-e] [-d] [-s] [-i] [-n]
                           [-o outfile] [-i]

Inspect the contents of a roCreate file

optional arguments:
  -h, --help            show this help message and exit
  -f file, --file file  The roCreate file to inspect
  -b bucket, --bucket-name bucket
                        S3 bucket name containing the roCreate file
  -k key, --key key      The file key for the roCreate file in the S3 bucket
  -t, --start-time       Show programme start time
  -e, --end-time         Show programme end time
  -d, --duration         Show total running order duration
  -s, --stories          Show stories within the running order in the running order
  -i, --items             Show items within stories in the running order
  -n, --notes             Show notes within story items in the running order
```

2.9.4 mosromgr merge

```
usage: mosromgr merge [-h] [-f [files [files ...]]] [-b bucket] [-p prefix] [-s suffix]
                           [-o outfile] [-i]

Merge the provided MOS files

optional arguments:
  -h, --help            show this help message and exit
  -f [files [files ...]], --files [files [files ...]]
                        The MOS files to merge
  -b bucket, --bucket-name bucket
                        S3 bucket name containing MOS files
  -p prefix, --prefix prefix
                        The file prefix for MOS files in the S3 bucket
  -s suffix, --suffix suffix
                        The file suffix for MOS files in the S3 bucket
  -o outfile, --outfile outfile
                        Output to a file
  -i, --incomplete      Allow an incomplete collection
```

2.10 Uses of mosromgr

This section lists projects which have been known to use the *mosromgr* module. If you have used *mosromgr* in a project and would like to add it to the list, please [edit this file](#) and open a pull request, [open an issue](#), or send an email to [bbcnewslabteam@bbc.co.uk](mailto:bbcnewslabsteam@bbc.co.uk).

2.10.1 BBC News Labs - MOS pipeline

We have a collection of AWS services making up a pipeline which processes MOS messages in real time, updates a status dashboard, publishes completed MOS running orders and JSON summaries to an internal document store, and populates a directory of programmes with new episodes and lists of stories (complete with timing information) as they become available.

Status dashboard:

completed (201)		pending (219)		warning (26)		mos error (100)		error (1)	
RO ID	RO Slug	Files	Brand Title	Episode Title	First Seen		Last Seen		
OPENMEDIA_NCS.W1.BBC.MOS.OM_10.1889085	34D 1400B WORLD AT ONE ARABIC TV NEWS Sat, 10.04.2021	457			Sat, 10 Apr 2021 11:07:34 GMT (30 minutes ago)		Sat, 10 Apr 2021 13:01:35 GMT (30 minutes ago)		
OPENMEDIA_NCS.W1.BBC.MOS.OM_4.15057195	1400 NEWS CHANNEL into Dateline Sat, 10.04.2021	329			Sat, 10 Apr 2021 11:29:19 GMT (8 minutes ago)		Sat, 10 Apr 2021 12:32:27 GMT (8 minutes ago)		
OPENMEDIA_NCS.W1.BBC.MOS.OM_3.13586968	1300 W5 Newshour Sat, 10.04.2021	674	Newshour		Sat, 10 Apr 2021 09:27:25 GMT (2 hours ago)		Sat, 10 Apr 2021 12:04:20 GMT (2 hours ago)		
OPENMEDIA_NCS.W1.BBC.MOS.OM_10.1889561	54D 1400 PERSIAN 1:30MIN SUMMARY Panorama Smartphones Sat, 10.04.2021	35			Sat, 10 Apr 2021 11:07:45 GMT (12 minutes from now)		Sat, 10 Apr 2021 12:03:18 GMT (12 minutes from now)		
OPENMEDIA_NCS.W1.BBC.MOS.OM_2.11680615	1300 BBC ONE LUNCHTIME Sat, 10.04.2021	167			Sat, 10 Apr 2021 10:33:17 GMT (an hour ago)		Sat, 10 Apr 2021 11:24:49 GMT (an hour ago)		
OPENMEDIA_NCS.W1.BBC.MOS.OM_10.1889328	34D 1300B ARABIC TV NEWS Sat, 10.04.2021	49			Sat, 10 Apr 2021 10:45:12 GMT (52 minutes ago)		Sat, 10 Apr 2021 11:01:19 GMT (52 minutes ago)		
OPENMEDIA_NCS.W1.BBC.MOS.OM_10.1889297	34D 1230B ARABIC TV NEWS Sat, 10.04.2021	238			Sat, 10 Apr 2021 10:20:21 GMT (an hour ago)		Sat, 10 Apr 2021 10:59:05 GMT (an hour ago)		
OPENMEDIA_NCS.W1.BBC.MOS.OM_4.15078416	1200 Studio B Pool feed Gun Salute Sat, 10.04.2021	310			Sat, 10 Apr 2021 07:02:11 GMT (4 hours ago)		Sat, 10 Apr 2021 10:54:16 GMT (4 hours ago)		
OPENMEDIA_NCS.W1.BBC.MOS.OM_10.1889271	34D 1200B ARABIC TV NEWS Sat, 10.04.2021	255			Sat, 10 Apr 2021 09:16:24 GMT (2 hours ago)		Sat, 10 Apr 2021 10:31:07 GMT (2 hours ago)		
OPENMEDIA_NCS.W1.BBC.MOS.OM_3.13587232	1100 W5 The Newsroom NEW Sat, 10.04.2021	462	The Newsroom		Sat, 10 Apr 2021 08:14:17 GMT (3 hours ago)		Sat, 10 Apr 2021 09:33:57 GMT (3 hours ago)		
OPENMEDIA_NCS.W1.BBC.MOS.OM_10.1889339	34D 1100B ARABIC TV NEWS Sat, 10.04.2021	87			Sat, 10 Apr 2021 08:30:15 GMT (3 hours ago)		Sat, 10 Apr 2021 09:11:28 GMT (3 hours ago)		
OPENMEDIA_NCS.W1.BBC.MOS.OM_4.15057142	1000 NEWS CHANNEL Sat, 10.04.2021	471			Sat, 10 Apr 2021 07:15:40 GMT (4 hours ago)		Sat, 10 Apr 2021 09:00:38 GMT (4 hours ago)		
OPENMEDIA_NCS.W1.BBC.MOS.OM_10.1889245	34D 1000B ARABIC TV NEWS Sat, 10.04.2021	342			Sat, 10 Apr 2021 07:09:21 GMT (4 hours ago)		Sat, 10 Apr 2021 08:31:31 GMT (4 hours ago)		
OPENMEDIA_NCS.W1.BBC.MOS.OM_10.1889074	34D 0930B MOBILE ARABIC TV NEWS Sat, 10.04.2021	32			Sat, 10 Apr 2021 07:07:12 GMT (4 hours ago)		Sat, 10 Apr 2021 07:09:16 GMT (4 hours ago)		
OPENMEDIA_NCS.W1.BBC.MOS.OM_10.1888921	34D 0900B ARABIC TV NEWS Sat, 10.04.2021	44			Sat, 10 Apr 2021 06:40:13 GMT (4 hours ago)		Sat, 10 Apr 2021 07:07:19 GMT (4 hours ago)		
OPENMEDIA_NCS.W1.BBC.MOS.OM_4.15057457	0555 NEWS CHANNEL JUNCTION Studio E 5at, 10.04.2021	23			Fri, 09 Apr 2021 23:54:10 GMT (11 hours ago)		Sat, 10 Apr 2021 07:02:14 GMT (11 hours ago)		
OPENMEDIA_NCS.W1.BBC.MOS.OM_10.1889043	34D 0830B ARABIC TV NEWS Sat, 10.04.2021	135			Sat, 10 Apr 2021 06:20:18 GMT (5 hours ago)		Sat, 10 Apr 2021 06:58:45 GMT (5 hours ago)		
OPENMEDIA_NCS.W1.BBC.MOS.OM_5.576296	0700 R4 TODAY (SAT) Sat, 10.04.2021	470	Today		Sat, 10 Apr 2021 03:05:17 GMT (8 hours ago)		Sat, 10 Apr 2021 06:01:02 GMT (8 hours ago)		
OPENMEDIA_NCS.W1.BBC.MOS.OM_4.15023784	1100 NEWS CHANNEL + BBC Two Tue, 30.03.2021	405			Fri, 09 Apr 2021 23:15:14 GMT (12 hours ago)		Sat, 10 Apr 2021 03:28:14 GMT (12 hours ago)		
OPENMEDIA_NCS.W1.BBC.MOS.OM_7.3665584	OUTLOOK Thu, 08.04.2021 FAMILY SECRETS	12	Outlook		Wed, 07 Apr 2021 02:09:11 GMT (3 days ago)		Sat, 10 Apr 2021 03:06:14 GMT (3 days ago)		

BBC NEWS LABS Privacy notice | Find us | Submit feedback |

Programmes directory:



BBC News



BBC News at One



BBC News at Six



BBC News at Ten



Focus on Africa

MIDLANDS
TODAY
BBC NEWS

Newsbeat



NEWSDAY



Newshour



Newsnight



Outlook



PM



Six O'Clock News



The Andrew Marr Show



The Fifth Floor

THE
NEWSROOM

The World Tonight



Today



Weekend



WOMAN'S HOUR



World at One



You and Yours

Example chapterised breakdown of an episode of [Newsnight](#):

BBC | mosromgr | Programmes Directory

Back to Newsnight

Newsnight: 09/04/2021



The day's important national and international news stories. With Kirsty Wark.

Stories in this episode

序号	操作	节目名称	时长	日期
1	PLAY	PROGRAMME SETUP	0:00:00	2021-04-09T21:45:00+01:00
2	PLAY	MENU	0:00:00	2021-04-09T21:45:00+01:00
3	PLAY	PRINCE PHILIP	0:00:12	2021-04-09T21:45:12+01:00
4	PLAY	PERCEPTION	0:00:54	2021-04-09T21:45:54+01:00
5	PLAY	BALMORAL	0:00:54	2021-04-09T21:45:54+01:00
6	PLAY	BALMORAL FLOAT PICS	0:01:27	2021-04-09T21:46:27+01:00
7	PLAY	BALMORAL	0:01:27	2021-04-09T21:46:27+01:00
8	PLAY	MONARCHY	0:01:27	2021-04-09T21:46:27+01:00
9	PLAY	FUTURE OF MONARCHY	0:01:51	2021-04-09T21:46:51+01:00
10	PLAY	PAPERS	0:01:51	2021-04-09T21:46:51+01:00
11	PLAY	PRINCE PHILIP MARRIAGE	0:02:55	2021-04-09T21:47:55+01:00
12	PLAY	END OF PROGRAMME	0:04:51	2021-04-09T21:49:51+01:00
13	PLAY	TEMPLATES	0:04:51	2021-04-09T21:49:51+01:00

BBC NEWS LABS Privacy notice | Find us | Submit feedback

2.10.2 BBC News Labs - Live Segment Notifications

We developed a proof-of-concept in which a note within a story in a running order could trigger a tweet to alert people of an upcoming story in time to watch live, or link to the clip of the story on-demand:

2.11 Changelog

Warning: Note that the library is currently in beta. The API and CLI are not yet stable and may change. Once the library reaches v1.0, it will be considered stable. Please consider giving [Feedback](#) to help stabilise the API.

2.11.1 Release 0.8.1 (2021-04-14)

- Fixup release

2.11.2 Release 0.8.0 (2021-04-13)

- Improved validation and error handling when merging various *MosFile* objects
- Added more arguments to CLI commands
- Corrected some singular *MosFile API - MOS Elements* properties that should have been lists (e.g. `source_story` should have been `source_stories`)

2.11.3 Release 0.7.0 (2021-01-08)

- Ensured exceptions are raised when story IDs are not found when merging
- Ensured tags aren't overwritten when they are empty in *MetaDataReplace*
- Ensured target story is found when merging *StoryInsert* and *StoryReplace*
- Added *RunningOrderControl* class (for roCtrl messages)
- Changed *tx_time* to *start_time*

2.11.4 Release 0.6.0 (2020-12-01)

- Added support for <StoryDuration> as an alternative to <MediaTime> and <TextTime>

2.11.5 Release 0.5.0 (2020-11-30)

- Added *ReadyToAir* MOS Type
- Improved error message on invalid *MosCollection*

2.11.6 Release 0.4.0 (2020-11-30)

- Changed *closed* property to *completed*
- Added transmission time and offset to *Story* class
- New *Command line interface* with separate commands for detect, inspect and merge
- Make MosCollection raise exceptions on failure, not just warnings

2.11.7 Release 0.3.0 (2020-11-24)

- Switched from complicated *__init__* constructors to multiple *from_* classmethods e.g. *from_file()*
- Replaced *get_mos_object* function with detection logic in the *MosFile* and *ElementAction* base classes
- Replaced *MosContainer* class with *MosCollection*

2.11.8 Release 0.2.0 (2020-11-24)

- Added *API - MOS Elements* - a collection of classes used to provide easy access to certain elements within a *MosFile* object

2.11.9 Release 0.1.0 (2020-11-24)

- Implemented most standard MOS message types as *MosFile* subclasses, supporting merging subsequent messages into the original running order
- Implemented a MOS file detection function (`get_mos_object`)
- Added a `MOSContainer` class as a wrapper for a complete programme
- Added a CLI for merging MOS files

2.12 Development

This page contains reference material for those interested in developing and contributing to the **mosromgr** module.

The project source code is hosted on GitHub at <https://github.com/bbc/mosromgr> which also includes the issue tracker.

2.12.1 Setting up for Development

1. Clone the repository and enter the directory:

```
$ git clone https://github.com/bbc/mosromgr  
$ cd mosromgr
```

2. Create a virtual environment e.g. using `virtualenvwrapper`:

```
$ mkvirtualenv mosromgr
```

3. Install the project for development:

```
$ make develop
```

After completing these steps, the library and command line interface will be available to use within your environment. Any modifications made to the source code will be automatically reflected within the environment.

2.12.2 Tests

The test suite uses `pytest`. Tests are organised mirroring the source code.

Running the tests

To run the linter, test suite and coverage analysis, activate the environment and run:

```
$ make test
```

For more control when running tests, run `pytest` directly, for example `pytest -vvxk story` will run tests with `story` in the name (`-k story`) with verbose output (`-vv`), and stop at the first failure (`-x`).

2.12.3 Documentation

The documentation is built using [sphinx](#) using the [diataxis](#) framework.

Building the documentation

To build the documentation, activate the environment and run:

```
$ make doc
```

This will generate the required diagrams and build the HTML docs which will be located in `docs/build/html`. Serve them with the command:

```
$ make doc-serve
```

You'll now be able to open the docs on your browser at <http://localhost:8000/>.

2.13 Feedback

Before we release v1.0 and stabilise the API, we are seeking other organisations using the MOS protocol to test `mosromgr` on their own MOS files and provide feedback so we can integrate any necessary changes to make sure it works effectively beyond the BBC's use.

If you can help, please test the module on your own MOS files and report back to us using our [discussion board](#) or issue tracker on GitHub, or email us at [bbcnewslabteam@bbc.co.uk](mailto:bbcnewslabsteam@bbc.co.uk).

2.14 Indices and tables

- genindex
- modindex
- search

**CHAPTER
THREE**

ISSUES AND QUESTIONS

Questions can be asked on the [discussion board](#), and issues can be raised on the [issue tracker](#).

**CHAPTER
FOUR**

CONTRIBUTING

Source code can be found on GitHub at github.com/bbc/mosromgr.

Contributions are welcome. Please refer to the [contributing guidelines](#).

CHAPTER

FIVE

CONTRIBUTORS

- Ben Nuttall
- Owen Tourlamain
- Rob French
- Lucy MacGlashan
- Dave Bevan

**CHAPTER
SIX**

LICENCE

Licensed under the [Apache License, Version 2.0](#).

**CHAPTER
SEVEN**

CONTACT

To get in touch with the maintainers, please contact the BBC News Labs team: bbcnewslabsteam@bbc.co.uk



PYTHON MODULE INDEX

m

`mosromgr.exc`, 52
`mosromgr.moscollection`, 49
`mosromgr.moselements`, 47
`mosromgr.mostypes`, 13
`mosromgr.utils`, 51

INDEX

Symbols

—add__() (mosromgr.mostypes.RunningOrder method), 14
—add__() (mosromgr.mostypes.RunningOrderReplace method), 41
—gt__() (mosromgr.mostypes.EAItemDelete method), 32
—gt__() (mosromgr.mostypes.EAItemInsert method), 35
—gt__() (mosromgr.mostypes.EAItemMove method), 39
—gt__() (mosromgr.mostypes.EAItemReplace method), 30
—gt__() (mosromgr.mostypes.EAItemSwap method), 37
—gt__() (mosromgr.mostypes.EAStoryDelete method), 31
—gt__() (mosromgr.mostypes.EAStoryInsert method), 34
—gt__() (mosromgr.mostypes.EAStoryMove method), 38
—gt__() (mosromgr.mostypes.EAStoryReplace method), 29
—gt__() (mosromgr.mostypes.EAStorySwap method), 36
—gt__() (mosromgr.mostypes.ItemDelete method), 23
—gt__() (mosromgr.mostypes.ItemInsert method), 24
—gt__() (mosromgr.mostypes.ItemMoveMultiple method), 26
—gt__() (mosromgr.mostypes.ItemReplace method), 27
—gt__() (mosromgr.mostypes.MetaDataReplace method), 22
—gt__() (mosromgr.mostypes.ReadyToAir method), 28
—gt__() (mosromgr.mostypes.RunningOrder method), 14
—gt__() (mosromgr.mostypes.RunningOrderControl method), 43
—gt__() (mosromgr.mostypes.RunningOrderEnd method), 42
—gt__() (mosromgr.mostypes.RunningOrderReplace method), 41
—gt__() (mosromgr.mostypes.StoryAppend method), 19
—gt__() (mosromgr.mostypes.StoryDelete method), 21
—gt__() (mosromgr.mostypes.StoryInsert method), 18
—gt__() (mosromgr.mostypes.StoryMove method), 20
—gt__() (mosromgr.mostypes.StoryReplace method), 16
—gt__() (mosromgr.mostypes.StorySend method), 15
—lt__() (mosromgr.mostypes.EAItemDelete method), 32
—lt__() (mosromgr.mostypes.EAItemInsert method), 35
—lt__() (mosromgr.mostypes.EAItemMove method), 39
—lt__() (mosromgr.mostypes.EAItemReplace method), 30
—lt__() (mosromgr.mostypes.EAItemSwap method), 37
—lt__() (mosromgr.mostypes.EAStoryDelete method), 31
—lt__() (mosromgr.mostypes.EAStoryInsert method), 34
—lt__() (mosromgr.mostypes.EAStoryMove method), 38
—lt__() (mosromgr.mostypes.EAStoryReplace method), 29
—lt__() (mosromgr.mostypes.EAStorySwap method), 36
—lt__() (mosromgr.mostypes.ItemDelete method), 23
—lt__() (mosromgr.mostypes.ItemInsert method), 24
—lt__() (mosromgr.mostypes.ItemMoveMultiple method), 26
—lt__() (mosromgr.mostypes.ItemReplace method), 27
—lt__() (mosromgr.mostypes.MetaDataReplace method), 22
—lt__() (mosromgr.mostypes.ReadyToAir method), 28
—lt__() (mosromgr.mostypes.RunningOrder method), 14

```
__lt__(mosromgr.mostypes.RunningOrderControl
      method), 43
__lt__(mosromgr.mostypes.RunningOrderEnd
      method), 42
__lt__(mosromgr.mostypes.RunningOrderReplace
      method), 41
__lt__(mosromgr.mostypes.StoryAppend method),
      19
__lt__(mosromgr.mostypes.StoryDelete method),
      21
__lt__(mosromgr.mostypes.StoryInsert method), 18
__lt__(mosromgr.mostypes.StoryMove method), 20
__lt__(mosromgr.mostypes.StoryReplace method),
      17
__lt__(mosromgr.mostypes.StorySend method), 15
__str__(mosromgr.moscollection.MosCollection
       method), 49
__str__(mosromgr.moselements.Item method), 48
__str__(mosromgr.moselements.MosElement
       method), 48
__str__(mosromgr.moselements.Story method), 47
__str__(mosromgr.mostypes.EAItemDelete
       method), 32
__str__(mosromgr.mostypes.EAItemInsert
       method), 35
__str__(mosromgr.mostypes.EAItemMove
       method), 40
__str__(mosromgr.mostypes.EAItemReplace
       method), 30
__str__(mosromgr.mostypes.EAItemSwap method),
      37
__str__(mosromgr.mostypes.EAStoryDelete
       method), 31
__str__(mosromgr.mostypes.EAStoryInsert
       method), 34
__str__(mosromgr.mostypes.EAStoryMove
       method), 38
__str__(mosromgr.mostypes.EAStoryReplace
       method), 29
__str__(mosromgr.mostypes.EAStorySwap
       method), 36
__str__(mosromgr.mostypes.ItemDelete method),
      23
__str__(mosromgr.mostypes.ItemInsert method),
      24
__str__(mosromgr.mostypes.ItemMoveMultiple
       method), 26
__str__(mosromgr.mostypes.ItemReplace method),
      27
__str__(mosromgr.mostypes.MetaDataReplace
       method), 22
__str__(mosromgr.mostypes.ReadyToAir method),
      28
__str__(mosromgr.mostypes.RunningOrder
      method), 14
__str__(mosromgr.mostypes.RunningOrderControl
      method), 43
__str__(mosromgr.mostypes.RunningOrderEnd
      method), 42
__str__(mosromgr.mostypes.RunningOrderReplace
      method), 41
__str__(mosromgr.mostypes.StoryAppend method),
      19
__str__(mosromgr.mostypes.StoryDelete method),
      21
__str__(mosromgr.mostypes.StoryInsert method),
      18
__str__(mosromgr.mostypes.StoryMove method),
      20
__str__(mosromgr.mostypes.StoryReplace method),
      17
__str__(mosromgr.mostypes.StorySend method), 15
```

B

```
base_tag() (mosromgr.mostypes.EAItemDelete prop-
erty), 33
base_tag() (mosromgr.mostypes.EAItemInsert prop-
erty), 35
base_tag() (mosromgr.mostypes.EAItemMove prop-
erty), 40
base_tag() (mosromgr.mostypes.EAItemReplace
property), 31
base_tag() (mosromgr.mostypes.EAItemSwap prop-
erty), 38
base_tag() (mosromgr.mostypes.EAStoryDelete prop-
erty), 32
base_tag() (mosromgr.mostypes.EAStoryInsert prop-
erty), 34
base_tag() (mosromgr.mostypes.EAStoryMove prop-
erty), 39
base_tag() (mosromgr.mostypes.EAStoryReplace
property), 29
base_tag() (mosromgr.mostypes.EAStorySwap prop-
erty), 37
base_tag() (mosromgr.mostypes.ElementAction prop-
erty), 47
base_tag() (mosromgr.mostypes.ItemDelete prop-
erty), 24
base_tag() (mosromgr.mostypes.ItemInsert property),
      25
base_tag() (mosromgr.mostypes.ItemMoveMultiple
property), 26
base_tag() (mosromgr.mostypes.ItemReplace prop-
erty), 27
base_tag() (mosromgr.mostypes.MetaDataReplace
property), 23
```

base_tag() (*mosromgr.mostypes.MosFile* property), 46
 base_tag() (*mosromgr.mostypes.ReadyToAir* property), 28
 base_tag() (*mosromgr.mostypes.RunningOrder* property), 15
 base_tag() (*mosromgr.mostypes.RunningOrderControl* property), 44
 base_tag() (*mosromgr.mostypes.RunningOrderEnd* property), 43
 base_tag() (*mosromgr.mostypes.RunningOrderReplace* property), 41
 base_tag() (*mosromgr.mostypes.StoryAppend* property), 19
 base_tag() (*mosromgr.mostypes.StoryDelete* property), 22
 base_tag() (*mosromgr.mostypes.StoryInsert* property), 18
 base_tag() (*mosromgr.mostypes.StoryMove* property), 20
 base_tag() (*mosromgr.mostypes.StoryReplace* property), 17
 base_tag() (*mosromgr.mostypes.StorySend* property), 16
 base_tag_name() (*mosromgr.mostypes.EAItemDelete* property), 33
 base_tag_name() (*mosromgr.mostypes.EAItemInsert* property), 35
 base_tag_name() (*mosromgr.mostypes.EAItemMove* property), 40
 base_tag_name() (*mosromgr.mostypes.EAItemReplace* property), 31
 base_tag_name() (*mosromgr.mostypes.EAItemSwap* property), 38
 base_tag_name() (*mosromgr.mostypes.EAStoryDelete* property), 32
 base_tag_name() (*mosromgr.mostypes.EAStoryInsert* property), 34
 base_tag_name() (*mosromgr.mostypes.EAStoryMove* property), 39
 base_tag_name() (*mosromgr.mostypes.EAStoryReplace* property), 29
 base_tag_name() (*mosromgr.mostypes.EAStorySwap* property), 37
 base_tag_name() (*mosromgr.mostypes.ElementAction* property), 47
 base_tag_name() (*mosromgr.mostypes.ItemDelete* property), 24
 base_tag_name() (*mosromgr.mostypes.ItemInsert* property), 25
 base_tag_name() (*mosromgr.mostypes.ItemMoveMultiple* property), 26
 base_tag_name() (*mosromgr.mostypes.ItemReplace* property), 27
 base_tag_name() (*mosromgr.mostypes.MetaDataReplace* property), 23
 base_tag_name() (*mosromgr.mostypes.MosFile* property), 46
 base_tag_name() (*mosromgr.mostypes.RunningOrder* property), 15
 base_tag_name() (*mosromgr.mostypes.ReadyToAir* property), 28
 base_tag_name() (*mosromgr.mostypes.RunningOrderControl* property), 44
 base_tag_name() (*mosromgr.mostypes.RunningOrderEnd* property), 43
 base_tag_name() (*mosromgr.mostypes.RunningOrderReplace* property), 41
 base_tag_name() (*mosromgr.mostypes.StoryAppend* property), 19
 base_tag_name() (*mosromgr.mostypes.StoryDelete* property), 22
 base_tag_name() (*mosromgr.mostypes.StoryInsert* property), 18
 base_tag_name() (*mosromgr.mostypes.StoryMove* property), 20
 base_tag_name() (*mosromgr.mostypes.StoryReplace* property), 17
 base_tag_name() (*mosromgr.mostypes.StorySend* property), 16

C

completed() (*mosromgr.moscollection.MosCollection* property), 50
 completed() (*mosromgr.mostypes.RunningOrder* property), 15

D

dict() (*mosromgr.mostypes.EAItemDelete* property), 33
 dict() (*mosromgr.mostypes.EAItemInsert* property), 35
 dict() (*mosromgr.mostypes.EAItemMove* property), 40
 dict() (*mosromgr.mostypes.EAItemReplace* property), 31
 dict() (*mosromgr.mostypes.EAItemSwap* property), 38
 dict() (*mosromgr.mostypes.EAStoryDelete* property), 32
 dict() (*mosromgr.mostypes.EAStoryInsert* property), 34
 dict() (*mosromgr.mostypes.EAStoryMove* property), 39
 dict() (*mosromgr.mostypes.EAStoryReplace* property), 30
 dict() (*mosromgr.mostypes.EAStorySwap* property), 37
 dict() (*mosromgr.mostypes.ElementAction* property), 47
 dict() (*mosromgr.mostypes.ItemDelete* property), 24

dict () (*mosromgr.mostypes.ItemInsert* property), 25
dict () (*mosromgr.mostypes.ItemMoveMultiple* property), 26
dict () (*mosromgr.mostypes.ItemReplace* property), 27
dict () (*mosromgr.mostypes.MetaDataReplace* property), 23
dict () (*mosromgr.mostypes.MosFile* property), 46
dict () (*mosromgr.mostypes.ReadyToAir* property), 28
dict () (*mosromgr.mostypes.RunningOrder* property), 15
dict () (*mosromgr.mostypes.RunningOrderControl* property), 44
dict () (*mosromgr.mostypes.RunningOrderEnd* property), 43
dict () (*mosromgr.mostypes.RunningOrderReplace* property), 41
dict () (*mosromgr.mostypes.StoryAppend* property), 19
dict () (*mosromgr.mostypes.StoryDelete* property), 22
dict () (*mosromgr.mostypes.StoryInsert* property), 18
dict () (*mosromgr.mostypes.StoryMove* property), 21
dict () (*mosromgr.mostypes.StoryReplace* property), 17
dict () (*mosromgr.mostypes.StorySend* property), 16
DuplicateStoryWarning, 54
duration () (*mosromgr.moselements.Story* property), 47
duration () (*mosromgr.mostypes.RunningOrder* property), 15
duration () (*mosromgr.mostypes.RunningOrderReplace* property), 41

E

EAItemDelete (class in *mosromgr.mostypes*), 32
EAItemInsert (class in *mosromgr.mostypes*), 35
EAItemMove (class in *mosromgr.mostypes*), 39
EAItemReplace (class in *mosromgr.mostypes*), 30
EAItemSwap (class in *mosromgr.mostypes*), 37
EAStoryDelete (class in *mosromgr.mostypes*), 31
EAStoryInsert (class in *mosromgr.mostypes*), 34
EAStoryMove (class in *mosromgr.mostypes*), 38
EAStoryReplace (class in *mosromgr.mostypes*), 29
EAStorySwap (class in *mosromgr.mostypes*), 36
ElementAction (class in *mosromgr.mostypes*), 46
end_time () (*mosromgr.moselements.Story* property), 47
end_time () (*mosromgr.mostypes.RunningOrder* property), 15
end_time () (*mosromgr.mostypes.RunningOrderReplace* property), 42

F

find_child () (in module *mosromgr.utils.xml*), 52
from_file () (*mosromgr.mostypes.EAItemDelete* class method), 33

from_file () (*mosromgr.mostypes.EAItemInsert* class method), 35
from_file () (*mosromgr.mostypes.EAItemMove* class method), 40
from_file () (*mosromgr.mostypes.EAItemReplace* class method), 30
from_file () (*mosromgr.mostypes.EAItemSwap* class method), 37
from_file () (*mosromgr.mostypes.EAStoryDelete* class method), 31
from_file () (*mosromgr.mostypes.EAStoryInsert* class method), 34
from_file () (*mosromgr.mostypes.EAStoryMove* class method), 38
from_file () (*mosromgr.mostypes.EAStoryReplace* class method), 29
from_file () (*mosromgr.mostypes.EAStorySwap* class method), 36
from_file () (*mosromgr.mostypes.ElementAction* class method), 46
from_file () (*mosromgr.mostypes.ItemDelete* class method), 23
from_file () (*mosromgr.mostypes.ItemInsert* class method), 24
from_file () (*mosromgr.mostypes.ItemMoveMultiple* class method), 26
from_file () (*mosromgr.mostypes.ItemReplace* class method), 27
from_file () (*mosromgr.mostypes.MetaDataReplace* class method), 22
from_file () (*mosromgr.mostypes.MosFile* class method), 46
from_file () (*mosromgr.mostypes.ReadyToAir* class method), 28
from_file () (*mosromgr.mostypes.RunningOrder* class method), 14
from_file () (*mosromgr.mostypes.RunningOrderControl* class method), 43
from_file () (*mosromgr.mostypes.RunningOrderEnd* class method), 42
from_file () (*mosromgr.mostypes.RunningOrderReplace* class method), 41
from_file () (*mosromgr.mostypes.StoryAppend* class method), 19
from_file () (*mosromgr.mostypes.StoryDelete* class method), 21
from_file () (*mosromgr.mostypes.StoryInsert* class method), 18
from_file () (*mosromgr.mostypes.StoryMove* class method), 20
from_file () (*mosromgr.mostypes.StoryReplace* class method), 17
from_file () (*mosromgr.mostypes.StorySend* class method), 16

```

from_files () (mosromgr.moscollection.MosCollection from_s3 () (mosromgr.mostypes.StoryMove class
    class method), 49                                         method), 20
from_s3 () (mosromgr.moscollection.MosCollection from_s3 () (mosromgr.mostypes.StoryReplace class
    class method), 49                                         method), 17
from_s3 () (mosromgr.mostypes.EAItemDelete class from_s3 () (mosromgr.mostypes.StorySend class
    method), 33                                         method), 16
from_s3 () (mosromgr.mostypes.EAItemInsert class from_string () (mosromgr.mostypes.EAItemDelete
    method), 35                                         class method), 33
from_s3 () (mosromgr.mostypes.EAItemMove class from_string () (mosromgr.mostypes.EAItemInsert
    method), 40                                         class method), 35
from_s3 () (mosromgr.mostypes.EAItemReplace class from_string () (mosromgr.mostypes.EAItemMove
    method), 30                                         class method), 40
from_s3 () (mosromgr.mostypes.EAItemSwap class from_string () (mosromgr.mostypes.EAItemReplace
    method), 37                                         class method), 30
from_s3 () (mosromgr.mostypes.EAStoryDelete class from_string () (mosromgr.mostypes.EAItemSwap
    method), 31                                         class method), 38
from_s3 () (mosromgr.mostypes.EAStoryInsert class from_string () (mosromgr.mostypes.EAStoryDelete
    method), 34                                         class method), 32
from_s3 () (mosromgr.mostypes.EAStoryMove class from_string () (mosromgr.mostypes.EAStoryInsert
    method), 39                                         class method), 34
from_s3 () (mosromgr.mostypes.EAStoryReplace class from_string () (mosromgr.mostypes.EAStoryMove
    method), 29                                         class method), 39
from_s3 () (mosromgr.mostypes.EAStorySwap class from_string () (mosromgr.mostypes.EAStoryReplace
    method), 36                                         class method), 29
from_s3 () (mosromgr.mostypes.ElementAction class from_string () (mosromgr.mostypes.EAStorySwap
    method), 46                                         class method), 36
from_s3 () (mosromgr.mostypes.ItemDelete class from_string () (mosromgr.mostypes.ElementAction
    method), 23                                         class method), 46
from_s3 () (mosromgr.mostypes.ItemInsert class from_string () (mosromgr.mostypes.ItemDelete
    method), 25                                         class method), 24
from_s3 () (mosromgr.mostypes.ItemMoveMultiple from_string () (mosromgr.mostypes.ItemInsert class
    class method), 26                                         method), 25
from_s3 () (mosromgr.mostypes.ItemReplace class from_string () (mosromgr.mostypes.ItemMoveMultiple
    method), 27                                         class method), 26
from_s3 () (mosromgr.mostypes.MetaDataReplace from_string () (mosromgr.mostypes.ItemReplace
    class method), 22                                         class method), 27
from_s3 () (mosromgr.mostypes.MosFile class from_string () (mosromgr.mostypes.MetaDataReplace
    method), 46                                         class method), 22
from_s3 () (mosromgr.mostypes.ReadyToAir class from_string () (mosromgr.mostypes.MosFile class
    method), 28                                         method), 46
from_s3 () (mosromgr.mostypes.RunningOrder class from_string () (mosromgr.mostypes.ReadyToAir
    method), 14                                         class method), 28
from_s3 () (mosromgr.mostypes.RunningOrderControl from_string () (mosromgr.mostypes.RunningOrder
    class method), 43                                         class method), 15
from_s3 () (mosromgr.mostypes.RunningOrderEnd from_string () (mosromgr.mostypes.RunningOrderControl
    class method), 42                                         class method), 44
from_s3 () (mosromgr.mostypes.RunningOrderReplace from_string () (mosromgr.mostypes.RunningOrderEnd
    class method), 41                                         class method), 42
from_s3 () (mosromgr.mostypes.StoryAppend class from_string () (mosromgr.mostypes.RunningOrderReplace
    method), 19                                         class method), 41
from_s3 () (mosromgr.mostypes.StoryDelete class from_string () (mosromgr.mostypes.StoryAppend
    method), 21                                         class method), 19
from_s3 () (mosromgr.mostypes.StoryInsert class from_string () (mosromgr.mostypes.StoryDelete
    method), 18                                         class method), 21

```

```
from_string() (mosromgr:mostypes.StoryInsert class method), 18
from_string() (mosromgr:mostypes.StoryMove class method), 20
from_string() (mosromgr:mostypes.StoryReplace class method), 17
from_string() (mosromgr:mostypes.StorySend class method), 16
from_strings() (mosromgr:moscollection.MosCollection class method), 50
merge() (mosromgr:mostypes.ItemMoveMultiple method), 26
merge() (mosromgr:mostypes.ItemReplace method), 27
merge() (mosromgr:mostypes.MetaDataReplace method), 23
merge() (mosromgr:mostypes.ReadyToAir method), 28
merge() (mosromgr:mostypes.RunningOrderControl method), 44
merge() (mosromgr:mostypes.RunningOrderEnd method), 43
merge() (mosromgr:mostypes.RunningOrderReplace method), 41
merge() (mosromgr:mostypes.StoryAppend method), 19
merge() (mosromgr:mostypes.StoryDelete method), 21
merge() (mosromgr:mostypes.StoryInsert method), 18
merge() (mosromgr:mostypes.StoryMove method), 20
merge() (mosromgr:mostypes.StoryReplace method), 17
merge() (mosromgr:mostypes.StorySend method), 16
message_id() (mosromgr:moscollection.MosReader property), 50
message_id() (mosromgr:mostypes.EAItemDelete property), 33
message_id() (mosromgr:mostypes.EAItemInsert property), 36
message_id() (mosromgr:mostypes.EAItemMove property), 40
message_id() (mosromgr:mostypes.EAItemReplace property), 31
message_id() (mosromgr:mostypes.EAItemSwap property), 38
message_id() (mosromgr:mostypes.EAStoryDelete property), 32
message_id() (mosromgr:mostypes.EAStoryInsert property), 34
message_id() (mosromgr:mostypes.EAStoryMove property), 39
message_id() (mosromgr:mostypes.EAStoryReplace property), 30
message_id() (mosromgr:mostypes.EAStorySwap property), 37
message_id() (mosromgr:mostypes.ElementAction property), 47
message_id() (mosromgr:mostypes.ItemDelete property), 24
message_id() (mosromgr:mostypes.ItemInsert property), 25
message_id() (mosromgr:mostypes.ItemMoveMultiple property), 26
message_id() (mosromgr:mostypes.ItemReplace property), 27
message_id() (mosromgr:mostypes.MetaDataReplace property), 23
message_id() (mosromgr:mostypes.MosFile prop-
```

G

```
get_file_contents() (in module mosromgr.utils.s3), 51
get_mos_files() (in module mosromgr.utils.s3), 51
```

I

```
id() (mosromgr:moselements.Item property), 48
id() (mosromgr:moselements.MosElement property), 48
id() (mosromgr:moselements.Story property), 47
insert_node() (in module mosromgr.utils.xml), 52
InvalidMosCollection, 53
Item (class in mosromgr:moselements), 48
ItemDelete (class in mosromgr:mostypes), 23
ItemInsert (class in mosromgr:mostypes), 24
ItemMoveMultiple (class in mosromgr:mostypes), 25
ItemNotFoundWarning, 53
ItemReplace (class in mosromgr:mostypes), 27
items() (mosromgr:moselements.Story property), 47
```

M

```
merge() (mosromgr:moscollection.MosCollection method), 50
merge() (mosromgr:mostypes.EAItemDelete method), 33
merge() (mosromgr:mostypes.EAItemInsert method), 35
merge() (mosromgr:mostypes.EAItemMove method), 40
merge() (mosromgr:mostypes.EAItemReplace method), 30
merge() (mosromgr:mostypes.EAItemSwap method), 38
merge() (mosromgr:mostypes.EAStoryDelete method), 32
merge() (mosromgr:mostypes.EAStoryInsert method), 34
merge() (mosromgr:mostypes.EAStoryMove method), 39
merge() (mosromgr:mostypes.EAStoryReplace method), 29
merge() (mosromgr:mostypes.EAStorySwap method), 36
merge() (mosromgr:mostypes.ItemDelete method), 24
merge() (mosromgr:mostypes.ItemInsert method), 25
```

erty), 46
 message_id () (*mosromgr:mostypes.ReadyToAir property*), 29
 message_id () (*mosromgr:mostypes.RunningOrder property*), 15
 message_id () (*mosromgr:mostypes.RunningOrderControl property*), 44
 message_id () (*mosromgr:mostypes.RunningOrderEnd property*), 43
 message_id () (*mosromgr:mostypes.RunningOrderReplace property*), 42
 message_id () (*mosromgr:mostypes.StoryAppend property*), 19
 message_id () (*mosromgr:mostypes.StoryDelete property*), 22
 message_id () (*mosromgr:mostypes.StoryInsert property*), 18
 message_id () (*mosromgr:mostypes.StoryMove property*), 21
 message_id () (*mosromgr:mostypes.StoryReplace property*), 17
 message_id () (*mosromgr:mostypes.StorySend property*), 16
 MetaDataReplace (*class in mosromgr:mostypes*), 22
 module
 mosromgr.exc, 52
 mosromgr.moscollection, 49
 mosromgr.moselements, 47
 mosromgr:mostypes, 13
 mosromgr.utils, 51
 mos_object () (*mosromgr:moscollection.MosReader property*), 50
 mos_readers () (*mosromgr:moscollection.MosCollection property*), 50
 mos_type () (*mosromgr:moscollection.MosReader property*), 50
 MosCollection (*class in mosromgr:moscollection*), 49
 MosCompletedMergeError, 53
 MosElement (*class in mosromgr:moselements*), 48
 MosFile (*class in mosromgr:mostypes*), 46
 MosInvalidXML, 53
 MosMergeError, 52
 MosReader (*class in mosromgr:moscollection*), 50
 mosromgr.exc
 module, 52
 mosromgr.moscollection
 module, 49
 mosromgr.moselements
 module, 47
 mosromgr:mostypes
 module, 13
 mosromgr.utils
 module, 51

MosRoMgrException, 52
 MosRoMgrWarning, 53

N

note () (*mosromgr:moselements.Item property*), 48

O

offset () (*mosromgr:moselements.Story property*), 48

R

ReadyToAir (*class in mosromgr:mostypes*), 28
 remove_node () (*in module mosromgr.utils.xml*), 51
 replace_node () (*in module mosromgr.utils.xml*), 51
 ro () (*mosromgr:moscollection.MosCollection property*), 50
 ro_id () (*mosromgr:moscollection.MosCollection property*), 50
 ro_id () (*mosromgr:moscollection.MosReader property*), 50
 ro_id () (*mosromgr:mostypes.EAItemDelete property*), 33
 ro_id () (*mosromgr:mostypes.EAItemInsert property*), 36
 ro_id () (*mosromgr:mostypes.EAItemMove property*), 40
 ro_id () (*mosromgr:mostypes.EAItemReplace property*), 31
 ro_id () (*mosromgr:mostypes.EAItemSwap property*), 38
 ro_id () (*mosromgr:mostypes.EAStoryDelete property*), 32
 ro_id () (*mosromgr:mostypes.EAStoryInsert property*), 34
 ro_id () (*mosromgr:mostypes.EAStoryMove property*), 39
 ro_id () (*mosromgr:mostypes.EAStoryReplace property*), 30
 ro_id () (*mosromgr:mostypes.EAStorySwap property*), 37
 ro_id () (*mosromgr:mostypes.ElementAction property*), 47
 ro_id () (*mosromgr:mostypes.ItemDelete property*), 24
 ro_id () (*mosromgr:mostypes.ItemInsert property*), 25
 ro_id () (*mosromgr:mostypes.ItemMoveMultiple property*), 26
 ro_id () (*mosromgr:mostypes.ItemReplace property*), 27
 ro_id () (*mosromgr:mostypes.MetaDataReplace property*), 23
 ro_id () (*mosromgr:mostypes.MosFile property*), 46
 ro_id () (*mosromgr:mostypes.ReadyToAir property*), 29
 ro_id () (*mosromgr:mostypes.RunningOrder property*), 15

ro_id() (*mosromgr.mostypes.RunningOrderControl property*), 44
ro_id() (*mosromgr.mostypes.RunningOrderEnd property*), 43
ro_id() (*mosromgr.mostypes.RunningOrderReplace property*), 42
ro_id() (*mosromgr.mostypes.StoryAppend property*), 20
ro_id() (*mosromgr.mostypes.StoryDelete property*), 22
ro_id() (*mosromgr.mostypes.StoryInsert property*), 18
ro_id() (*mosromgr.mostypes.StoryMove property*), 21
ro_id() (*mosromgr.mostypes.StoryReplace property*), 17
ro_id() (*mosromgr.mostypes.StorySend property*), 16
ro_slug() (*mosromgr.moscollection.MosCollection property*), 50
ro_slug() (*mosromgr.mostypes.MetaDataReplace property*), 23
ro_slug() (*mosromgr.mostypes.RunningOrder property*), 15
ro_slug() (*mosromgr.mostypes.RunningOrderReplace property*), 42
RunningOrder (*class in mosromgr.mostypes*), 14
RunningOrderControl (*class in mosromgr.mostypes*), 43
RunningOrderEnd (*class in mosromgr.mostypes*), 42
RunningOrderReplace (*class in mosromgr.mostypes*), 41

source_stories() (*mosromgr.mostypes.StoryInsert property*), 18
source_story() (*mosromgr.mostypes.EAStoryReplace property*), 30
source_story() (*mosromgr.mostypes.StoryMove property*), 21
source_story() (*mosromgr.mostypes.StoryReplace property*), 17
start_time() (*mosromgr.moselements.Story property*), 48
start_time() (*mosromgr.mostypes.RunningOrder property*), 15
start_time() (*mosromgr.mostypes.RunningOrderReplace property*), 42
stories() (*mosromgr.mostypes.EAStoryDelete property*), 32
stories() (*mosromgr.mostypes.EAStorySwap property*), 37
stories() (*mosromgr.mostypes.RunningOrder property*), 15
stories() (*mosromgr.mostypes.RunningOrderReplace property*), 42
stories() (*mosromgr.mostypes.StoryAppend property*), 20
stories() (*mosromgr.mostypes.StoryDelete property*), 22
Story (*class in mosromgr.moselements*), 47
story() (*mosromgr.mostypes.RunningOrderControl property*), 44
story() (*mosromgr.mostypes.StorySend property*), 16
StoryAppend (*class in mosromgr.mostypes*), 19
StoryDelete (*class in mosromgr.mostypes*), 21
StoryInsert (*class in mosromgr.mostypes*), 18
StoryMove (*class in mosromgr.mostypes*), 20
StoryNotFoundWarning, 53
StoryReplace (*class in mosromgr.mostypes*), 16
StorySend (*class in mosromgr.mostypes*), 15

S

slug() (*mosromgr.moselements.Item property*), 48
slug() (*mosromgr.moselements.MosElement property*), 48
slug() (*mosromgr.moselements.Story property*), 48
source_item() (*mosromgr.mostypes.EAItemMove property*), 40
source_items() (*mosromgr.mostypes.EAItemDelete property*), 33
source_items() (*mosromgr.mostypes.EAItemInsert property*), 36
source_items() (*mosromgr.mostypes.EAItemReplace property*), 31
source_items() (*mosromgr.mostypes.EAItemSwap property*), 38
source_items() (*mosromgr.mostypes.ItemInsert property*), 25
source_items() (*mosromgr.mostypes.ItemMoveMultiple property*), 26
source_items() (*mosromgr.mostypes.ItemReplace property*), 27
source_stories() (*mosromgr.mostypes.EAStoryInsert property*), 34
source_stories() (*mosromgr.mostypes.EAStoryMove property*), 39

</div

target_story() (<i>mosromgr:mostypes.EAItemDelete property</i>), 33	xml() (<i>mosromgr:mostypes.ItemMoveMultiple property</i>), 26
target_story() (<i>mosromgr:mostypes.EAItemInsert property</i>), 36	xml() (<i>mosromgr:mostypes.ItemReplace property</i>), 28
target_story() (<i>mosromgr:mostypes.EAItemMove property</i>), 40	xml() (<i>mosromgr:mostypes.MetaDataReplace property</i>), 23
target_story() (<i>mosromgr:mostypes.EAItemReplace property</i>), 31	xml() (<i>mosromgr:mostypes.MosFile property</i>), 46
target_story() (<i>mosromgr:mostypes.EAItemSwap property</i>), 38	xml() (<i>mosromgr:mostypes.ReadyToAir property</i>), 29
target_story() (<i>mosromgr:mostypes.EAStoryInsert property</i>), 35	xml() (<i>mosromgr:mostypes.RunningOrder property</i>), 15
target_story() (<i>mosromgr:mostypes.EAStoryMove property</i>), 39	xml() (<i>mosromgr:mostypes.RunningOrderControl property</i>), 44
target_story() (<i>mosromgr:mostypes.EAStoryReplace property</i>), 30	xml() (<i>mosromgr:mostypes.RunningOrderEnd property</i>), 43
target_story() (<i>mosromgr:mostypes.ItemDelete property</i>), 24	xml() (<i>mosromgr:mostypes.RunningOrderReplace property</i>), 42
target_story() (<i>mosromgr:mostypes.ItemInsert property</i>), 25	xml() (<i>mosromgr:mostypes.StoryAppend property</i>), 20
target_story() (<i>mosromgr:mostypes.ItemMoveMultiple property</i>), 26	xml() (<i>mosromgr:mostypes.StoryDelete property</i>), 22
target_story() (<i>mosromgr:mostypes.ItemReplace property</i>), 28	xml() (<i>mosromgr:mostypes.StoryInsert property</i>), 19
target_story() (<i>mosromgr:mostypes.StoryMove property</i>), 21	xml() (<i>mosromgr:mostypes.StoryMove property</i>), 21
target_story() (<i>mosromgr:mostypes.StoryReplace property</i>), 17	xml() (<i>mosromgr:mostypes.StoryReplace property</i>), 17
	xml() (<i>mosromgr:mostypes.StorySend property</i>), 16

U

UnknownMosFileType, 52

X

xml() (<i>mosromgr:moselements.Item property</i>), 48
xml() (<i>mosromgr:moselements.MosElement property</i>), 48
xml() (<i>mosromgr:moselements.Story property</i>), 48
xml() (<i>mosromgr:mostypes.EAItemDelete property</i>), 33
xml() (<i>mosromgr:mostypes.EAItemInsert property</i>), 36
xml() (<i>mosromgr:mostypes.EAItemMove property</i>), 40
xml() (<i>mosromgr:mostypes.EAItemReplace property</i>), 31
xml() (<i>mosromgr:mostypes.EAItemSwap property</i>), 38
xml() (<i>mosromgr:mostypes.EAStoryDelete property</i>), 32
xml() (<i>mosromgr:mostypes.EAStoryInsert property</i>), 35
xml() (<i>mosromgr:mostypes.EAStoryMove property</i>), 39
xml() (<i>mosromgr:mostypes.EAStoryReplace property</i>), 30
xml() (<i>mosromgr:mostypes.EAStorySwap property</i>), 37
xml() (<i>mosromgr:mostypes.ElementAction property</i>), 47
xml() (<i>mosromgr:mostypes.ItemDelete property</i>), 24
xml() (<i>mosromgr:mostypes.ItemInsert property</i>), 25